

SAFETY DATA SHEET

ALPHALOXAN FARBE Basis W05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : ALPHALOXAN FARBE Basis W05

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses				
Professional use Consumer use				
	Uses advised against			
None				

Product use : Mineral coating for exterior use.

1.3 Details of the supplier of the safety data sheet

Akzo Nobel Coatings S.p.A. Via Pietro Nenni 14, 28053 Castelletto sopra Ticino, Tel. +39 0331 916611

Internet: www.sikkens.it

e-mail address of person responsible for this SDS

: servizio.clienti@akzonobel.com

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : Centri Antiveleni per il territorio italiano:

CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA - Roma

- Tel. 06 68593726

CAV Az. Osp. Univ. Foggia - Foggia - Tel. 800183459 CAV Az. Osp. "A. Cardarelli" - Napoli - Tel. 081-5453333 CAV Policlinico "Umberto I" - Roma - Tel. 06-49978000 CAV Policlinico "A. Gemelli" - Roma - Tel. 06-3054343

CAV Az. Osp. "Careggi" U.O. Tossicologia Medica - Firenze - Tel. 055-7947819 CAV Centro Nazionale di Informazione Tossicologica - Pavia - Tel. 0382-24444

AkzoNobel

CAV Osp. Niguarda Ca' Granda - Milano - Tel. 02-66101029

CAV Azienda Ospedaliera Papa Giovanni XXII - Bergamo - Tel. 800883300 CAV Azienda Ospedaliera Integrata Verona - Verona - Tel. 800011858

Date of issue/Date of revision: 25-4-2024Version: 1Date of previous issue: No previous validation1/20

ALPHALOXAN FARBE Basis W05

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements: H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

General: P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention: P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national or international regulations.

Supplemental label

elements

: Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1) and octhilinone (ISO). May produce an allergic reaction. Warning! Hazardous respirable droplets may be

: This mixture does not contain any substances that are assessed to be a PBT or a

formed when sprayed. Do not breathe spray or mist.

Annex XVII - Restrictions

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according

vPvB.

to Regulation (EC) No. 1907/2006, Annex XIII

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Date of issue/Date of revision : 25-4-2024 Version : 1

Date of previous issue : No previous validation 2/20 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥15 - ≤20	Carc. 2, H351 (inhalation)	-	[1] [*]
IPBC	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	<0.1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.5 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5	<0.05	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 500 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 10	[1]
isoproturon (ISO)	EC: 251-835-4 CAS: 34123-59-6 Index: 006-044-00-7	≤0.051	Carc. 2, H351 STOT RE 2, H373 (blood) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 10 M [Chronic] = 10	[1]
bronopol (INN)	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	≤0.1	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400	ATE [Oral] = 500 mg/kg ATE [Dermal] = 1100 mg/kg M [Acute] = 10	[1]
terbutryn	EC: 212-950-5 CAS: 886-50-0	≤0.017	Acute Tox. 4, H302 Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 500 mg/kg M [Acute] = 100 M [Chronic] = 100	[1]
CMIT/MIT(3:1)	REACH #: 01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Skin Irrit. 2, H315: $0.06\% \le C < 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319:	[1]

Date of issue/Date of revision: 25-4-2024Version: 1Date of previous issue: No previous validation3/20AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 3: Composition/information on ingredients								
				0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100				
OIT	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	<0.001	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 125 mg/kg ATE [Dermal] = 311 mg/kg ATE [Inhalation (dusts and mists)] = 0.27 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]			

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a physical, health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses if easy to do. Get medical

attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting

unless directed to do so by medical personnel.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

 Date of issue/Date of revision
 : 25-4-2024
 Version
 : 1

 Date of previous issue
 : No previous validation
 4/20
 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 4: First aid measures

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1), octhilinone (ISO). May produce an allergic reaction.

Over-exposure signs/symptoms

: No specific data. Eye contact Inhalation : No specific data. Skin contact : No specific data. Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion

products

Decomposition products may include the following materials:

metal oxide/oxides

5.3 Advice for firefighters

Special protective actions

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Date of issue/Date of revision : 25-4-2024 Version : 1

AkzoNobel Date of previous issue : No previous validation 5/20

ALPHALOXAN FARBE Basis W05

SECTION 6: Accidental release measures

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

Date of issue/Date of revision : 25-4-2024 Version : 1

Date of previous issue : No previous validation 6/20 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
IPBC	DNEL	Long term	0.023 mg/	Workers	Systemic
		Inhalation	m³		
	DNEL	Short term	0.07 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Short term	1.16 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Long term Inhalation	1.16 mg/m³		Local
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Dermal	0.345 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.966 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.2 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	6.81 mg/m ³	Workers	Systemic
	DATE	Inhalation	0.004	0	1 1
bronopol (INN)	DNEL	Short term Dermal	0.004 mg/	General	Local
	DNEL	Long term Dermal	cm ² 0.004 mg/	population General	Local
	DINEL	Long term Dermai	cm ²	population	Lucai
	DNEL	Short term Dermal	0.008 mg/	Workers	Local
	DIVLL	Onort term berman	cm ²	VVOIKCIS	Local
	DNEL	Long term Dermal	0.008 mg/	Workers	Local
			cm ²		
	DNEL	Long term Oral	0.18 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Short term Oral	0.5 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Short term	0.6 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	0.6 mg/m ³	General	Systemic
	D	Inhalation	0.7 "	population	
	DNEL	Long term Dermal	0.7 mg/kg	General	Systemic
			bw/day	population	
<u> </u>	ı	I	I	l	ı

Date of issue/Date of revision : 25-4-2024 Version : 1 7/20

Date of previous issue : No previous validation **AkzoNobel**

ALPHALOXAN FARBE Basis W05

SECTION 8:	Exposure	controls/	personal	protection
01010	LAPOGGIO		porcoriai	protoction

•					
	DNEL	Short term Inhalation	1.8 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	2 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	2.1 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	2.5 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	2.5 mg/m ³	Workers	Local
	DNEL	Long term	3.5 mg/m ³	Workers	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	10.5 mg/m ³	Workers	Systemic
CMIT/MIT(3:1)	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.02 mg/m ³		Local
	DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m ³		Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic
<u></u>		Į			

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

 Date of issue/Date of revision
 : 25-4-2024
 Version
 : 1

 Date of previous issue
 : No previous validation
 8/20
 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 8: Exposure controls/personal protection

When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended.

Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust

ventilation, suitable respiratory protective equipment should be used.

Environmental exposure

Body protection

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

limit

Physical state : Liquid.
Color : White.

Odor : Characteristic.

Odor threshold : Not available.

Melting point/freezing point : Not available.

Boiling point, initial boiling point, and boiling range

Flammability : Not available.

Lower and upper explosion : Not available.

Flash point : Not available.

Auto-ignition temperature :

Date of issue/Date of revision : 25-4-2024 Version : 1

Date of previous issue : No previous validation 9/20 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
2-[(2-methoxy-4-nitrophenyl)azo]-N- (2-methoxyphenyl)-3-oxobutyramide	180	356	VDI 2263
tributylamine	210	410	EU A.15
2-(2-methoxyethoxy)ethanol	215	419	DIN 51794

Decomposition temperature : Not available.

Hq : 8 [Conc. (% w/w): 100%] [DIN EN 1262]

Viscosity : Kinematic (room temperature): 1015 mm²/s [DIN EN ISO 3219]

Kinematic (40°C): Not applicable. [DIN EN ISO 3219]

Solubility(ies)

Media Result cold water Soluble [OECD (TG 105)]

Partition coefficient: n-octanol/ : Not applicable.

water

Vapor pressure

	Vapor Pressure at 20°C		Va	e at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
ammonia	360.03	48				
methanol	126.96	16.9				
ethanol	42.95	5.7				

Relative density : 1.577

Vapor density : Not available.

Particle characteristics

Median particle size : Not applicable.

Percentage of particles with aerodynamic diameter ≤ 10

SECTION 10: Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 25-4-2024 Version : 1

AkzoNobel Date of previous issue : No previous validation 10/20

ALPHALOXAN FARBE Basis W05

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, CMIT/MIT(3:1), octhilinone (ISO). May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
IPBC	LD50 Oral	Rat	1470 mg/kg	-
1,2-benzisothiazol-3(2H)-one	LD50 Oral	Mouse	1150 mg/kg	-
	LD50 Oral	Rat	1020 mg/kg	_
bronopol (INN)	LC50 Inhalation Dusts and mists	Rat	800 mg/m ³	4 hours
	LD50 Dermal	Mouse	4750 mg/kg	_
	LD50 Dermal	Rat	64 mg/kg	_
	LD50 Intraperitoneal	Mouse	32.8 mg/kg	_
	LD50 Intraperitoneal	Mouse	15500 µg/kg	-
	LD50 Intraperitoneal	Rat	22 mg/kg	-
	LD50 Intraperitoneal	Rat	26 mg/kg	-
	LD50 Intravenous	Mouse	48 mg/kg	-
	LD50 Intravenous	Rat	37400 µg/kg	-
	LD50 Oral	Mouse	270 mg/kg	-
	LD50 Oral	Mouse	194 mg/kg	-
	LD50 Oral	Rabbit	190 mg/kg	-
	LD50 Oral	Rat	180 mg/kg	-
	LD50 Oral	Rat	267 mg/kg	-
	LD50 Oral	Rat	254 mg/kg	-
	LD50 Oral	Rat	342 mg/kg	-
	LD50 Subcutaneous	Mouse	116 mg/kg	-
	LD50 Subcutaneous	Rat	170 mg/kg	-
	LD50 Subcutaneous	Rat	200 mg/kg	-
terbutryn	LD50 Dermal	Rabbit	>10200 mg/kg	-
	LD50 Intraperitoneal	Mouse	554 mg/kg	-
	LD50 Intraperitoneal	Rat	699 mg/kg	-
	LD50 Oral	Mouse	3884 mg/kg	-
	LD50 Oral	Rat	2045 mg/kg	-
OIT	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-

Conclusion/Summary

: Not available.

Acute toxicity estimates

 Date of issue/Date of revision
 : 25-4-2024
 Version
 : 1

 Date of previous issue
 : No previous validation
 11/20
 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
IPBC	500	N/A	N/A	N/A	0.5
1,2-benzisothiazol-3(2H)-one	500	N/A	N/A	N/A	0.05
bronopol (INN)	500	1100	N/A	N/A	N/A
terbutryn	500	N/A	N/A	N/A	N/A
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05
OIT	125	311	N/A	N/A	0.27

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bronopol (INN)	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Moderate irritant	Rabbit	-	80 mg	-
terbutryn	Eyes - Moderate irritant	Rabbit	-	76 mg	-
-	Skin - Mild irritant	Rabbit	-	380 mg	-
OIT	Eyes - Severe irritant	Rabbit	-	100 mg	-

Conclusion/Summary

: Not available.

Sensitization

Conclusion/Summary

: Not available.

Mutagenicity

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
bronopol (INN)	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
	Category 1	-	larynx
isoproturon (ISO)	Category 2	-	blood

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.

Date of issue/Date of revision : 25-4-2024 Version : 1

Date of previous issue : No previous validation 12/20 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 11: Toxicological information

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
titanium dioxide	Acute LC50 >1000 mg/l Fresh water	Fish - Pimephales promelas	96 hours
IPBC	Acute EC50 956 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 0.16 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
	Acute LC50 2920 ppb Marine water	Crustaceans - Neomysis mercedis - Adult	48 hours
	Acute LC50 40 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 95 ppb Marine water	Fish - Oncorhynchus kisutch - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Acute LC50 100 ppb Fresh water	Fish - Oncorhynchus mykiss -	96 hours

 Date of issue/Date of revision
 : 25-4-2024
 Version
 : 1

 Date of previous issue
 : No previous validation
 13/20
 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION	12:	Ecological	information
---------	-----	-------------------	-------------

SECTION 12: Ecologi	cai information		
		Juvenile (Fledgling, Hatchling,	
		Weanling)	
	Acute LC50 72 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 67 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 67 µg/l Fresh water	Fish - Oncorhynchus mykiss -	96 hours
		Juvenile (Fledgling, Hatchling,	
		Weanling)	
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days
1,2-benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
	_	dubia	
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
bronopol (INN)	Acute EC50 0.02 ppm Fresh water	Algae - Desmodesmus	96 hours
		subspicatus	
	Acute EC50 0.41 ppm Fresh water	Algae - Navicula pelliculosa	96 hours
	Acute EC50 0.22 ppm Fresh water	Algae - Pseudokirchneriella	96 hours
		subcapitata	
	Acute EC50 0.18 ppm Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 1.6 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 36 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 11.17 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 41.5 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 20 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 26.4 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days
	Chronic NOEC 1.94 ppm	Fish - Oncorhynchus mykiss	49 days
terbutryn	Acute EC50 3.1 µg/l Marine water	Algae - Dunaliella tertiolecta	96 hours
	Acute EC50 0.1 µg/l Fresh water	Algae - Fragilaria capucina ssp.	96 hours
	. 0	rumpens	
	Acute EC50 2 μg/l Fresh water	Algae - Pseudokirchneriella	72 hours
	. 5	subcapitata	
	Acute EC50 3.3 µg/l Fresh water	Algae - Pseudokirchneriella	72 hours
		subcapitata	
	Acute EC50 2.7 µg/l Fresh water	Algae - Pseudokirchneriella	96 hours
		subcapitata	
	Acute EC50 2.66 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 7100 μg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 579.3 mg/l Fresh water	Crustaceans - Pacifastacus	48 hours
		leniusculus - Juvenile (Fledgling,	
		Hatchling, Weanling)	
	Acute LC50 1400 μg/l Fresh water	Fish - Carassius carassius	96 hours
	Acute LC50 1.5 ppm Marine water	Fish - Cyprinodon variegatus	96 hours
	Acute LC50 2.4 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.82 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1800 μg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
OIT	Acute EC10 0.000224 mg/l	Algae - Navicula peliculosa	48 hours
	Acute EC50 0.084 mg/l	Algae - Desmodesmus	72 hours
		subspicatus	
	Acute EC50 0.00129 mg/l	Algae - Navicula peliculosa	48 hours
	Acute EC50 0.42 mg/l	Daphnia	48 hours
	Acute EC50 107 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 180 ppb Fresh water	Daphnia - Daphnia magna	48 hours
_ I	l	1	<u> </u>

Date of issue/Date of revision
Date of previous issue

: 25-4-2024

: No previous validation

Version : 1

14/20

AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 12: Ecological information			
	Acute EC50 320 ppb Fresh water Acute LC50 154 ppb Fresh water Acute LC50 47 ppb Fresh water Acute LC50 50 ppb Fresh water Acute LC50 65.5 ppb Fresh water Acute LC50 140 ppb Fresh water Chronic NOEC 8.5 ppb	Daphnia - Daphnia magna Fish - Notemigonus crysoleucas Fish - Oncorhynchus mykiss Fish - Oncorhynchus mykiss Fish - Oncorhynchus mykiss Fish - Pimephales promelas Fish - Pimephales promelas	48 hours 96 hours 96 hours 96 hours 96 hours 96 hours 35 days

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary: Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
isoproturon (ISO)	2.87	-	low
bronopol (INN)	0.18	-	low
terbutryn	3.74	-	low
OIT	2.45	-	low

12.4 Mobility in soil

Soil/water partition

coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal: The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities

with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Date of issue/Date of revision: 25-4-2024Version: 1Date of previous issue: No previous validation15/20AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 13: Disposal considerations

Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no

longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation	
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11	

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Disposal considerations

: Using information provided in this safety data sheet, advice should be obtained from

the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or

national legal provisions.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG
14.1 UN number or ID number	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-
14.3 Transport hazard class(es)	-	-
14.4 Packing group	-	-
14.5 Environmental hazards	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not applicable.

Date of issue/Date of revision : 25-4-2024 Version : 1 **AkzoNobel** Date of previous issue : No previous validation 16/20

ALPHALOXAN FARBE Basis W05

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions: Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the

product label and/or technical data sheet for further information.

VOC for Ready-for-Use

Mixture

: Not available.

Industrial emissions

(integrated pollution

: Not listed

prevention and control) -Air

Industrial emissions

: Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Biocidal products regulation

D.Lgs. 152/06 : Not determined.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

Date of issue/Date of revision : 25-4-2024 Version : 1

AkzoNobel Date of previous issue : No previous validation 17/20

ALPHALOXAN FARBE Basis W05

SECTION 15: Regulatory information

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety

:

: No Chemical Safety Assessment has been carried out.

Assessment

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated
	exposure.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Date of issue/Date of revision : 25-4-2024 Version : 1

Date of previous issue : No previous validation 18/20 AkzoNobel

ALPHALOXAN FARBE Basis W05

SECTION 16: Other information

Acute Tox. 2 ACUTE TOXICITY - Category 2 Acute Tox. 3 **ACUTE TOXICITY - Category 3** Acute Tox. 4 **ACUTE TOXICITY - Category 4**

Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1 Aduatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2 Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3

Carc. 2 **CARCINOGENICITY - Category 2** Eve Dam. 1

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN CORROSION/IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1C SKIN CORROSION/IRRITATION - Category 2

SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SKIN SENSITIZATION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 1

SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 2

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -

Category 3

Date of printing : 25-4-2024 Date of issue/ Date of : 25-4-2024

revision

Skin Corr. 1

Skin Irrit. 2

Skin Sens. 1

Skin Sens. 1A

Skin Sens. 1B

STOT RE 1

STOT RE 2

STOT SE 3

Skin Corr. 1C

Date of previous issue : No previous validation

Version : 1

: 0E4D234B630B1EEEBEC9EAC54E9153E8 **Unique ID**

Notice to reader

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

Date of issue/Date of revision : 25-4-2024 Version : 1

AkzoNobel Date of previous issue : No previous validation 19/20

ALPHALOXAN FARBE Basis W05

Date of issue/Date of revision: 25-4-2024Version: 1Date of previous issue: No previous validation20/20

AkzoNobel