

FRESKO

Revitalizing oil for varnished wood

3265-in January. 2016

Description

Product:FRESKO is a solvent-based revitalizing oil for varnished wood, free from active ingredients.

Fields of use:particularly suitable for "refreshing" and restoring shine to wooden surfaces and other substrates, previously painted with solvent-based and water-based products and opacified by bad weather, when flaking phenomena have not yet occurred. The product is also applicable indoors.

Tint:00-colorless.

Packaging:0.750 and 2.5 Liters.

Technical data

Specific weight:ca. 0.83 kg / l, at +20 °

C. Flash point:ca. 41 ° C.

Viscosity:ca. 65 s, Ford cup, 2 mm (approx. 12 s, DIN 53211 cup, 4 mm), at +20 ° C.

Brilliance: shiny.

Drying: dust free after approx. 1 hour, dry after approx. 12 hours, depending on the quantity applied and the weather. With low temperatures and / or high humidity, the drying time increases proportionally.

Odor:own faint smell; odorless after drying.

Storage:5 years in original closed packaging. Keep cool, but protected from frost. Close partially used jars well; if the bladder is excessively large, transfer to smaller containers.

Application Notes

Generality:mix the product well before use.

Application systems:brush. **Preparation of the**

substrate: the surfaces to be treated must be dry and free from dust and grease; if necessary wash thoroughly with a mild detergent and rinse very well. **Application**

temperature: Application tips5 - 35 ° C
no particular advice.

Recommended cycles:

- Renewals on wood inside and outside:	clean and lightly sand the surface to improve adhesion. Then 1 x FRESKO.
--	---

It is always advisable to check the state of the external coatings within 2 years of application, especially that of the artifacts exposed to the south-west.

Consumption: ca. 15 m² / l per coat.

Dilution: FRESKO is ready for use by brush; if necessary, dilute with a synthetic thinner.

Cleaning of tools: with thinner for synthetics or nitro thinner, immediately after use.

Special instructions

During application, protect your face, hands and eyes and ensure sufficient ventilation. Cover switches and power lines well to avoid short circuits. Avoid working near open flames or sparks. In case of insufficient ventilation, wear a respiratory mask (half mask with interchangeable filters, filter class A1, identification color brown).

FRESKO

Revitalizing oil for varnished wood

3265-in January. 2016

Risk phrases: Flammable (R 10). Contains white spirit. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R 51/53). Repeated exposure may cause skin dryness and cracking (R 66). Inhalation of vapors may cause drowsiness and dizziness (R 67).

Contains butanone oxime and phthalic acid. It can generate allergic reactions.

Precautionary advice: Keep out of the reach of children (S 2). Do not breathe vapors / aerosols (S 23). Avoid contact with skin and eyes (S 24/25). Do not throw the residues in the sewers but take the material and its container to a disposal center for hazardous waste (S 29/56). If swallowed, seek medical advice immediately and show him the container or label (S 46). Use only in well-ventilated areas (S 51). This material and its container must be disposed of as hazardous waste (S 60). Do not apply near flames and sparks. In case of contact with eyes, rinse immediately with plenty of water. In case of contact with skin, wash immediately with soap and water. Do not throw residues into sewers, water and the ground. Do not dispose of with household waste.

In case of spillage of the product, collect the liquid with absorbent material and dispose of according to the regulations in force.

European waste catalog: 08 01 11. **Water hazard class:** Classification according to VbF: A II. **ADR / RID:** UN 1263, paintings, 3, III, WGK 2, dangerous for water (Self-classification).

The aforementioned indications correspond to the most recent state of the art in development and use. Since the use and application of the products are beyond our sphere of influence, we are only liable for the consistent quality of the products. If in doubt, please ask for our technical advice.