

# REFRESH Revitalizing oil for varnished wood

3054 - January 2016

## **Description**

Product:RINFRESKO is a revitalizing water-based oil for varnished wood, which gives varnished wood a new shine.

**Fields of use:**particularly suitable for "refreshing" and restoring brilliance to wooden surfaces and other painted substrates. It seals pores and capillary cracks in the paint film and in this way extends the duration over time. RINFRESKO makes the surface semi-gloss and if used annually it gives beauty and long life to the wood. **Tint:**00-colorless.

Packaging: 0.750 Liters.

#### Technical data

Specific weight:ca.  $1.02 \text{ g} / \text{cm}_3(+20 ^{\circ} \text{ C})$ .

Flash point: Viscosity: nd

46 - 48 s / DIN-, 2 mm, at +20 ° C.

**Trocknung:** dry to the touch after about 30 min .. With low temperatures and / or high humidity the drying time is stretches proportionally.

Odor:own faint smell; odorless after drying.

**Storage:**5 years in original closed packaging. Keep cool, but protected from frost. Close partially used jars well; if the bladder is excessively large, transfer to smaller containers.

### **Application Notes**

**Generality:**mix the product well before use.

**Application systems:** Thoroughly clean the surface with warm water and a few drops of neutral detergent. Rinse with a clean cloth and clear water. Always with a cloth then apply a thin layer evenly on the clean and dry surface.

**Application temperature:**  $10 - 35 \degree C$ 

**Consumptiorc**a. 15 m<sup>2</sup> / l per coat. **Dilution:** RINFRESKO is ready for use

**Cleaning of tools:** immediately after use with water

## **Special instructions**

Observe the instructions given in the safety data sheet. Even during the application of products low in harmful substances it is necessary to observe the usual precautions foreseen for painting works; always provide for sufficient ventilation. Cover switches and power lines well to avoid short circuits.

Use only water with mild soap or mild neutral detergents. Prevent the product from polluting water courses and waste water or from penetrating into the ground.

**Disposal:**Only dispose of perfectly clean containers to recycling centers. Do not dispose of dirty containers and material residues at special waste collection centers.

**European waste catalog**:n. 08 01 12 (waste colors and lacquers). Do not dispose of the product and its residues in sewers, surface water or on the ground.

Water hazard class: Classification WGK 1 slightly dangerous (Self-classification).

according to VbF:fails. ADR / RID:Not

applicable.

The aforementioned indications correspond to the most recent state of the art in development and use. Since the use and application of the products are beyond our sphere of influence, we are only liable for the consistent quality of the products. If in doubt, please ask for our technical advice.

