

Colorificio A. & B. Casati SpA

Revision n.10
 Revision date 04/08/2015
 Printed on 02/11/2015
 Page no. 1/11

IT

338000 - HOME-IMPREGNATING WOOD**Safety Data Sheet****SECTION 1. Identification of the substance / mixture and of the company / undertaking****1.1. Product identifier**

Code: **338000**
 Name: **HOUSE-WOOD IMPREGNATING**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description / Use: **Impregnating agent for wood.**

1.3. Information on the supplier of the safety data sheet

Business name: **Colorificio A. & B. Casati SpA Via**
 Address: **Valpantena 59 / B - Poiano**
 Location and State: **37142 VERONA ITALY (VR)**
 tel. **045 550 244**
 fax **045 550 414**
 e-mail of the competent person responsible for the safety data sheet: **tintotec@casati.it**

1.4. Emergency telephone number

For urgent information contact: **045550244**

SECTION 2. Hazards identification.**2.1. Substance or mixture classification.**

The product is classified as dangerous pursuant to the provisions of Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments). The product therefore requires a safety data sheet compliant with the provisions of Regulation (EC) 1907/2006 and subsequent amendments.

Any additional information regarding risks to health and / or the environment are given in sections. 11 and 12 of this sheet.

Hazard classification and indications:

Flammable liquid, category 3	H226	Flammable liquid and vapor.
Aspiration hazard, category 1	H304	It can be fatal if swallowed and if it enters the respiratory tract.
Specific target organ toxicity - single exposure, category 3	H336	It can cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements.

Danger labeling pursuant to Regulation (EC) 1272/2008 (CLP) and subsequent amendments and adjustments.

Hazard pictograms:**Warnings:**

Danger

Hazard statements:

H226	Flammable liquid and vapor.
H304	It can be fatal if swallowed and if it enters the respiratory tract. It can cause drowsiness or dizziness.
H336	
H412	Harmful to aquatic life with long lasting effects. Repeated exposure can cause skin dryness and cracking.
EUH066	

338000 - HOME-IMPREGNATING WOOD

SECTION 2. Hazards identification.... / >>

EUH208

Contains: 2-BUTANONE OXIME
It can cause an allergic reaction.

Precautionary advice:

P101

P102

P210

P233

P280

P301 + P310

P501

If you need to consult a doctor, have the container or the label of the product available. Keep out of reach of children.

Keep away from heat sources, hot surfaces, sparks, open flames or other sources of ignition. Not smoking. Keep the container tightly closed.

Wear protective gloves and protect eyes / face.

IF SWALLOWED: Immediately call a POISON CENTER / doctor / . . . Dispose of the product / container in collection points for hazardous or special waste.

Contains:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

2.3. Other dangers.

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

SECTION 3. Composition / information on ingredients.

3.1. Substances.

Not relevant information.

3.2. Blends.

Contains:

Identification.

Conc.%.
CAS.

Classification 1272/2008 (CLP).

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

CAS. 64742-48-9 62 - 66 Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066

THERE IS. 919-857-5

INDEX.

Reg. No. 01-2119463258-33

Hydrocarbons, C9, aromatics

CAS. 7 - 10

Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066

THERE IS. 918-668-5

INDEX.

Reg. No. 01-2119455851-35 1-METHYL-2-

METHOXYETHYL ACETATE CAS.

108-65-6 3 - 5

Flam. Liq. 3 H226

THERE IS. 203-603-9

INDEX. 607-195-00-7

Reg. No. 01-2119475791-29

2-BUTANONE OXIME

CAS. 96-29-7 0.3 - 0.35

Carc. 2 H351, Acute Tox. 4 H312, Eye Dam. 1 H318, Skin Sens. 1 H317

THERE IS. 202-496-6

INDEX. 616-014-00-0

Reg. No. 01-2119639477-28

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS.

64742-82-1 0.159 - 0.17

Flam. Liq. 3 H226, STOT RE 1 H372, Asp. Tox. 1 H304, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Note P

THERE IS. 919-446-0

INDEX. 649-330-00-2

Reg. No. 01-2119458049-33-XXXX 2-

(2-BUTOXYETHOXY) ETHANOL CAS.

112-34-5 0.069 - 0.08

Eye Irrit. 2 H319

THERE IS. 203-961-6

INDEX. 603-096-00-8

3-iodo-2-propinylbutylcarbamate

CAS. 55406-53-6 0.025 - 0.08

Acute Tox. 3 H331, Acute Tox. 4 H302, STOT RE 1 H372, Eye Dam. 1 H318, Skin Sens. 1 H317, Aquatic Acute 1 H400 M = 10, Aquatic Chronic 1 H410 M = 10

THERE IS. 259-627-5

INDEX.

338000 - HOME-IMPREGNATING WOOD**SECTION 3. Composition / information on ingredients.**

... / >>

XYLENE (MIXTURE OF ISOMERS)

CAS. 1330-20-7 0 - 0.01 Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Note C

THERE IS: 215-535-7

INDEX: 601-022-00-9

Reg. No. 01-2119488216-32

Note: Upper value of the range excluded.

The full wording of the hazard statements (H) is given in section 16 of the sheet.

SECTION 4. First aid measures.**4.1. Description of first aid measures.**

EYES: Remove any contact lenses. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids well. Consult a physician if the problem persists.

SKIN: Take off contaminated clothing. Take a shower immediately. Call a doctor immediately. Wash the contaminated garments before reusing them.

INHALATION: Take the subject to fresh air. If breathing stops, give artificial respiration. Call a doctor immediately.

INGESTION: Call a doctor immediately. Do not induce vomiting. Do not give anything that is not expressly authorized by your doctor.

4.2. Most important symptoms and effects, both acute and delayed.

For symptoms and effects due to the substances contained, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed. Information not available.**SECTION 5. Firefighting measures.****5.1. Fire fighting.** SUITABLE

EXTINGUISHING MEDIA

Extinguishing media are: carbon dioxide, foam, chemical powder. For product leaks and spills that have not caught fire, water spray can be used to disperse flammable vapors and protect those involved in stopping the leak.

UNSUITABLE EXTINGUISHING MEDIA

Do not use water jets. Water is not effective to extinguish the fire however it can be used to cool closed containers exposed to the flame, preventing bursts and explosions.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Overpressure can be created in containers exposed to fire with danger of explosion. Avoid breathing combustion products.

5.3. Recommendations for firefighters. GENERAL INFORMATION

Cool the containers with jets of water to avoid product decomposition and the development of substances potentially hazardous to health. Always wear full fire protection equipment. Collect the extinguishing water which must not be discharged into the sewers. Dispose of the contaminated water used for extinguishing and the residue of the fire according to current regulations.

EQUIPMENT

Normal clothing for firefighting, such as an open circuit compressed air breathing apparatus (EN 137), flame retardant suit (EN469), flame retardant gloves (EN 659) and fire brigade boots (HO A29 or A30).

SECTION 6. Accidental release measures.**6.1. Personal precautions, protective equipment and emergency procedures.** Stop the leak if there is no danger.

Wear suitable protective equipment (including personal protective equipment referred to in section 8 of the safety data sheet) to prevent contamination of skin, eyes and personal clothing. These indications are valid both for the workers and for emergency interventions.

6.2. Environmental precautions.

Prevent the product from entering sewers, surface water, groundwater.

6.3. Methods and materials for containment and cleaning up.

Suck up the leaked product into a suitable container. Evaluate the compatibility of the container to be used with the product, checking section 10. Absorb the remainder with inert absorbent material.

338000 - HOME-IMPREGNATING WOOD**SECTION 6. Accidental release measures.**

.../ >>

Provide sufficient ventilation of the place affected by the leak. Check for any incompatibilities for the container material in section 7. The disposal of contaminated material must be carried out in accordance with the provisions of point 13.

6.4. Reference to other sections.

Any information regarding personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.**7.1. Precautions for Safe Handling.**

Keep away from heat, sparks and open flames, do not smoke or use matches or lighters. Without adequate ventilation, vapors can accumulate on the ground and catch fire even at a distance, if triggered, with the risk of backfire. Avoid the accumulation of electrostatic charges. Do not eat, drink or smoke during use. Remove contaminated clothing and protective equipment before entering eating areas. Avoid the dispersion of the product in the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Keep only in the original container. Store in a cool and well-ventilated place, away from heat sources, open flames, sparks and other sources of ignition. Keep containers away from any incompatible materials, checking section 10.

7.3. Specific end uses.

Information not available.

SECTION 8. Exposure controls / personal protection.**8.1. Control parameters.**

Normative requirements:

THAT	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail 2012. / Grenzwerte am Arbeitsplatz EH40 /
GRB	United Kingdom	2005 Workplace exposure limits
IRL	Éire	Code of Practice Chemical Agent Regulations 2011
ITA	Italy	Legislative Decree 9 April 2008, n.81
EU	OEL EU	Directive 2009/161 / EU; Directive 2006/15 / EC; Directive 2004/37 / EC; Directive 2000/39 / EC.
	TLV-ACGIH	ACGIH 2014

1-METHYL-2-METHOXYETHYL ACETATE**Threshold limit value.**

Guy	State	TWA / 8h		STEL / 15min		
		mg / m ³	ppm	mg / m ³	ppm	
WEL	GRB	274	50	548	100	
OEL	IRL	275	50	550	100	LEATHER.
TLV	ITA	275	50	550	100	LEATHER.
OEL	EU	275	50	550	100	LEATHER.

2-BUTANONE OXIME**Threshold limit value.**

Guy	State	TWA / 8h		STEL / 15min		
		mg / m ³	ppm	mg / m ³	ppm	
OEL	IRL	10	3	33	10	

2- (2-BUTOXYETHOXY) ETHANOL**Threshold limit value.**

Guy	State	TWA / 8h		STEL / 15min		
		mg / m ³	ppm	mg / m ³	ppm	
VEL	THAT	67	10	101.2	15	
MAK	THAT	67	10	101.2	15	
TLV	ITA	67.5	10	101.2	15	
OEL	EU	67.5	10	101.2	15	
TLV-ACGIH		66	10			

338000 - HOME-IMPREGNATING WOOD**SECTION 8. Exposure controls / personal protection.**

... / >>

XYLENE (MIXTURE OF ISOMERS)**Threshold limit value.**

Guy	State	TWA / 8h		STEL / 15min		
		mg / m ³	ppm	mg / m ³	ppm	
WEL	GRB	220	50	441	100	
OEL	IRL	221	50	442	100	LEATHER.
TLV	ITA	221	50	442	100	LEATHER.
OEL	EU	221	50	442	100	LEATHER.
TLV-ACGIH		434	100	651	150	

Legend:

(C) = CEILING; INALAB = Inhalable Fraction; RESPIR = Breathing Fraction; TORAC = Thoracic Fraction.

8.2. Exposure controls.

Considering that the use of adequate technical measures should always take priority over personal protective equipment, ensure good ventilation in the workplace through effective local exhaust. Personal protective equipment must bear the CE mark which certifies their compliance with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (ref. Standard EN 374).

For the final choice of the material of the work gloves it is necessary to consider: compatibility, degradation, breakage time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is not foreseeable. Gloves have a wear time that depends on the duration and method of use.

SKIN PROTECTION

Wear category I professional long-sleeved work clothes and safety footwear (ref. Directive 89/686 / EEC and standard EN ISO 20344). Wash with soap and water after removing protective clothing.

Consider providing antistatic clothing if the workplace presents a risk of explosivity. **EYE PROTECTION**

It is recommended to wear airtight protective goggles (ref. Standard EN 166). **RESPIRATORY PROTECTION**

In case of exceeding the threshold value (e.g. TLV-TWA) of the substance or of one or more of the substances present in the product, it is advisable to wear a mask with a type A filter whose class (1, 2 or 3) must be chosen in relation to the limit concentration of use. (ref. standard EN 14387). If there are gases or vapors of a different nature and / or gases or vapors with particles (aerosols, fumes, mists, etc.), combined filters must be provided.

The use of respiratory protection means is necessary if the technical measures adopted are not sufficient to limit the exposure of the worker to the threshold values taken into consideration. The protection offered by the masks is however limited.

In the event that the substance in question is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear an open-circuit compressed air breathing apparatus (ref. Standard EN 137) or a self-contained breathing apparatus. outdoor air (ref. EN 138 standard). For the correct choice of the respiratory protection device, refer to the EN 529 standard.

ENVIRONMENTAL EXPOSURE CONTROLS.

Emissions from manufacturing processes, including those from ventilation equipment should be controlled for compliance with environmental protection legislation.

Product residues must not be discharged without control into waste water or water courses.

SECTION 9. Physical and chemical properties.**9.1. Information on basic physical and chemical properties.**

Physical state	liquid
Color	transparent
Odor	aliphatic hydrocarbons
Odor threshold.	Unavailable.
pH.	Unavailable.
Melting or freezing point. Initial	Unavailable.
boiling point.	Unavailable.
Boiling range. Flash	Unavailable.
point. Evaporation rate	$23 \leq T \leq 60$ ° C.
	Unavailable.
Flammability of solids and	Unavailable.
gases Lower flammability limit.	Unavailable.
Upper flammability limit. Lower	Unavailable.
explosive limit. Upper explosive	Unavailable.
limit. Vapor pressure.	Unavailable.
	Unavailable.
Vapor density	Unavailable.
Relative density.	0,850 Kg / l
Solubility	insoluble in water

338000 - HOME-IMPREGNATING WOOD**SECTION 9. Physical and chemical properties.... / >>**

Partition coefficient: n-octanol / water: Auto-	Unavailable.
ignition temperature.	Unavailable.
Decomposition temperature.	Unavailable.
Viscosity	Unavailable.
Explosive properties	Unavailable.
Oxidizing properties	Unavailable.

9.2. Other information. VOC

(Directive 2004/42 / EC): VOC	76.72% - 652.11	g / liter.
(volatile carbon):	available.	

SECTION 10. Stability and reactivity.**10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

1-METHYL-2-METHOXYETHYL ACETATE: stable, but with air it can slowly give peroxides which explode due to an increase in temperature.

10.2. Chemical stability.

The product is stable under normal conditions of use and storage.

10.3. Possibility of hazardous reactions.

Vapors can form explosive mixtures with air.

XYLENE: it is stable, but can give violent reactions in the presence of strong oxidants such as sulfuric and nitric acids, perchlorates. It can form explosive mixtures with air.

1-METHYL-2-METHOXYETHYL ACETATE: can react violently with oxidants and strong acids and alkali metals. 2- (2-BUTOXYETHOXY) ETHANOL: can react with oxidants. With atmospheric oxygen it can form peroxides. Upon reaction with aluminum it can give hydrogen. It can form explosive mixtures with air.

10.4. Conditions to avoid.

Avoid overheating. Avoid the accumulation of electrostatic charges. Avoid any source of ignition.

1-METHYL-2-METHOXYETHYL ACETATE: keep in an inert atmosphere and away from humidity because it hydrolyzes easily. 2- (2-BUTOXYETHOXY) ETHANOL: avoid contact with air.

10.5. Incompatible materials.

1-METHYL-2-METHOXYETHYL ACETATE: oxidants, strong acids and alkali metals. 2- (2-BUTOXYETHOXY) ETHANOL: oxidizing substances, strong acids and alkaline metals.

10.6. Hazardous decomposition products.

Due to thermal decomposition or in the event of fire, gases and vapors potentially harmful to health can be released.

2- (2-BUTOXYETHOXY) ETHANOL: hydrogen.

SECTION 11. Toxicological information.**11.1. Information on toxicological effects.**

In the absence of experimental toxicological data on the product itself, any health hazards of the product have been assessed on the basis of the properties of the substances contained, according to the criteria established by the reference legislation for classification. Therefore, consider the concentration of the individual dangerous substances possibly mentioned in sect. 3, to evaluate the toxicological effects deriving from exposure to the product.

The introduction of even small quantities of liquid into the respiratory system in case of ingestion or vomiting can cause bronchopneumonia and pulmonary edema.

The product contains very volatile substances that can cause significant depression of the central nervous system (CNS), with effects such as drowsiness, dizziness, loss of reflexes, narcosis.

By repeated exposure the product can exert a degreasing action on the skin, which manifests itself with dryness and cracking. The product contains sensitizing substance (s) and therefore may cause an allergic reaction.

XYLENE (MIXTURE OF ISOMERS): toxic action on the central nervous system (encephalopathies); irritant action on the skin, conjunctiva, cornea and respiratory system.

1-METHYL-2-METHOXYETHYL ACETATE: the main route of entry is the skin, while the respiratory one is less important, given the low vapor pressure of the product. Above 100 ppm there is irritation of the ocular, nasal and oropharyngeal mucous membranes. At 1000 ppm there are balance disturbances and severe eye irritation. Clinical and biological tests performed on the exposed volunteers did not reveal any anomalies. Acetate produces greater skin and eye irritation on direct contact. No chronic effects on humans are reported.

338000 - HOME-IMPREGNATING WOOD**SECTION 11. Toxicological information.... / >>**

2- (2-BUTOXYETHOXY) ETHANOL: can be absorbed by inhalation, ingestion and skin contact; it is irritating to the skin and especially to the eyes. Damage to the spleen can occur. At room temperature the danger of inhalation is unlikely, due to the low vapor pressure of the substance.

3-iodo-2-propinylbutylcarbamate

LD50 (Oral).	> 300 mg / kg
LD50 (Dermal).	> 2000 mg / kg
LC50 (Inhalation).	0.67 mg / l

Hydrocarbons, C9,

aromatics LD50 (Oral).	3592 mg / kg
LD50 (Dermal).	> 3160 mg / kg
LC50 (Inhalation).	> 6193 mg / m3

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral).	3523 mg / kg Rat
LD50 (Dermal).	4350 mg / kg Rabbit
LC50 (Inhalation).	26 mg / l / 4h Rat

1-METHYL-2-METHOXYETHYL ACETATE

LD50 (Oral).	8530 mg / kg Rat
LD50 (Dermal).	> 5000 mg / kg Rat

2- (2-BUTOXYETHOXY) ETHANOL

LD50 (Oral).	3384 mg / kg Rat
LD50 (Dermal).	2700 mg / kg Rabbit

2-BUTANONE OXIME

LD50 (Oral).	2400 mg / kg Rat
LD50 (Dermal).	> 1000 mg / kg Rabbit
LC50 (Inhalation).	20 mg / l / 4h Rat

Hydrocarbons,	C9-C12,	n-alkanes,	isoalkanes,	cyclical,	aromatic	(2-25%)
LD50 (Oral).	> 5000 mg / kg Rat					
LD50 (Dermal).	> 2000 mg / kg Rabbit					

SECTION 12. Ecological information.

The product is to be considered as dangerous for the environment and is harmful to aquatic organisms with long-term negative effects for the aquatic environment.

12.1. Toxicity.

3-iodo-2-propinylbutylcarbamate

LC50 - Fish.	0.067 mg / l / 96h
EC50 - Crustaceans.	0.65 mg / l / 48h
EC50 - Algae / Aquatic Plants.	0.053 mg / l / 72h
Chronic NOEC for Pisces.	0.0084 mg / l
Chronic NOEC Crustaceans.	0.05 mg / l
Chronic NOEC for Algae / Aquatic Plants.	0.053 mg / l / 72h

Hydrocarbons, C9, aromatics

EC50 - Crustaceans.	3.2 mg / l / 48h
---------------------	------------------

Hydrocarbons,

C9-C12,	n-alkanes,	isoalkanes,	cyclical,	aromatic	(2-25%)
LC50 - Pisces.	8.2 mg / l / 96h	Pimephales promelas			
EC50 - Crustaceans.	4.5 mg / l / 48h	Daphnia magna			
EC50 - Algae / Aquatic Plants.	3.1 mg / l / 72h	Pseudokirchnerella subcapitata			

12.2. Persistence and degradability.

XYLENE (MIXTURE OF ISOMERS)

Solubility in water.	mg / l 100 - 1000
Biodegradability: Data not available.	

338000 - HOME-IMPREGNATING WOOD**SECTION 12. Ecological information.... / >>****1-METHYL-2-METHOXYETHYL ACETATE**

Solubility in water. > 10000 mg / l

Quickly biodegradable.

2- (2-BUTOXYETHOXY) ETHANOL

Solubility in water. mg / l 1000 - 10000

Quickly biodegradable.

2-BUTANONE OXIME

Solubility in water. mg / l 1000 - 10000

Inherently biodegradable.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclical, aromatic (2-25%)
Quickly biodegradable.

12.3. Bioaccumulation potential.

XYLENE (MIXTURE OF ISOMERS) Partition
coefficient: n-octanol / water. BCF.

3.12
25.9**1-METHYL-2-METHOXYETHYL ACETATE**

Partition coefficient: n-octanol / water. 1.2

2- (2-BUTOXYETHOXY) ETHANOL

Partition coefficient: n-octanol / water. 1

2-BUTANONE OXIME

Partition coefficient: n-octanol / water. BCF.
0.63
0.5

12.4. Mobility in soil.

XYLENE (MIXTURE OF ISOMERS) Partition
coefficient: soil / water.

2.73

2-BUTANONE OXIME

Partition coefficient: soil / water. 0.55

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclical, aromatic (2-25%)
Partition coefficient: soil / water. 1.78

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.**13.1. Waste treatment methods.**

Reuse if possible. Product residues are to be considered special hazardous waste. The dangerousness of the waste that partially contains this product must be assessed on the basis of the laws in force.

Disposal must be entrusted to an authorized waste management company, in compliance with national and possibly local regulations.

The transport of waste may be subject to ADR.

CONTAMINATED PACKAGING

Contaminated packaging must be sent for recovery or disposal in compliance with national waste management regulations.

SECTION 14. Transport information.**14.1. UN number.**

ADR / RID, IMDG, IATA: 1263

338000 - HOME-IMPREGNATING WOOD**SECTION 14. Transport information.... / >>****14.2. UN proper shipping name.**

ADR / RID: PAINTS or MATERIALS SIMILAR TO PAINT
IMDG: PAINT or PAINT RELATED MATERIAL PAINT or
IATA: PAINT RELATED MATERIAL

14.3. Transport hazard classes.

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3

**14.4. Packing group.**

ADR / RID, IMDG, IATA: III

14.5. Dangers for the environment.

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for users.

ADR / RID:	HIN - Kemler: 30 Special provision: 640E EMS: FE, S	Limited Quantity: 5 L	Tunnel restriction code: (D / E)
IMDG:	-AND	Limited quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packing instructions: 366
	Pass .:	Maximum quantity: 60 L	Packing instructions: 355
	Special instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code.

Not relevant information.

SECTION 15. Regulatory information.**15.1. Standards and legislation on health, safety and environment specific for the substance or mixture.**

Seveso category. 6

Restrictions relating to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006.

Product.

Point. 3 - 40

Contained substances.

Point. 55 2- (2-BUTOXYETHOXY) ETHANOL

Substances in the Candidate List (Art. 59 REACH).

None.

Substances subject to authorization (Annex XIV REACH).

None.

Substances subject to export notification obligation Reg. (EC) 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

338000 - HOME-IMPREGNATING WOOD**SECTION 15. Regulatory information.**

... / >>

Sanitary checks.

Workers exposed to this chemical agent dangerous to health must be subjected to health surveillance carried out in accordance with the provisions of art. 41 of Legislative Decree 81 of 9 April 2008 unless the risk to the safety and health of the worker has been assessed as irrelevant, in accordance with the provisions of art. 224 paragraph 2.

VOC (Directive 2004/42 / EC):

Wood impregnating agents that form a film of minimal thickness.

VOC expressed in g / liter of ready-to-use product:

Maximum limit:

700.00 (2010)

VOC of the product:

652.11

15.2. Chemical safety assessment.

A chemical safety assessment has not been developed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in sections 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Carc. 2	Carcinogenicity, category 2 Acute
Acute Tox. 3	toxicity, category 3 Acute toxicity,
Acute Tox. 4	category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1 Aspiration
Asp. Tox. 1	hazard, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2 Skin
Skin Irrit. 2	irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3 Skin
Skin Sens. 1	sensitization, category 1
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H226	Liquid and flammable vapors.
H351	Suspected of causing cancer.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure. It can be
H304	fatal if swallowed and if it enters the respiratory tract. Causes serious eye
H318	damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	It can irritate the respiratory tract.
H317	May cause an allergic skin reaction. It can
H336	cause drowsiness or dizziness.
H400	Very toxic to aquatic organisms.
H410	Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with
H411	long lasting effects. Harmful to aquatic life with long lasting effects.
H412	Repeated exposure can cause skin dryness and cracking.
EUH066	

LEGEND:

- ADR: European agreement for the transport of dangerous goods by road
- CAS NUMBER: Number of the Chemical Abstract Service
- EC50: Concentration that gives effect to 50% of the population subject to testing
- CE NUMBER: Identification number in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived no effect level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System for Classification and Labeling of Chemicals
- IATA DGR: Regulations for the transport of dangerous goods of the International Air Transport Association
- IC50: Concentration of immobilization of 50% of the population subject to testing
- IMDG: International maritime code for the transport of dangerous goods
- IMO: International Maritime Organization

338000 - HOME-IMPREGNATING WOOD**SECTION 16. Other information.... / >>**

- INDEX NUMBER: Identification number in Annex VI of the CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- OEL: Occupational exposure level
- PBT: Persistent, bioaccumulating and toxic according to REACH
- PEC: Predicted environmental concentration
- PEL: Predictable level of exposure
- PNEC: Predicted No Effect Concentration
- REACH: EC Regulation 1907/2006
- RID: Regulations for the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration which must not be exceeded during any moment of occupational exposure.
- TWA STEL: Short term exposure limit
- TWA: Weighted average exposure limit
- VOC: Volatile organic compound
- vPvB: Very persistent and very bioaccumulating according to REACH
- WGK: Water hazard class (Germany).

GENERAL BIBLIOGRAPHY:

1. Regulation (EU) 1907/2006 of the European Parliament (REACH)
 2. Regulation (EU) 1272/2008 of the European Parliament (CLP)
 3. Regulation (EU) 790/2009 of the European Parliament (I Atp. CLP)
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 of the European Parliament (II Atp. CLP)
 6. Regulation (EU) 618/2012 of the European Parliament (III Atp. CLP)
 7. Regulation (EU) 487/2013 of the European Parliament (IV Atp. CLP)
 8. Regulation (EU) 944/2013 of the European Parliament (V Atp. CLP)
 9. Regulation (EU) 605/2014 of the European Parliament (VI Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - NI Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA Agency website

Note for the user:

The information contained in this sheet is based on the knowledge available to us at the date of the latest version. The user must ensure the suitability and completeness of the information in relation to the specific use of the product.

This document should not be construed as a guarantee of any specific property of the product.

Since the use of the product does not fall under our direct control, the user is obliged to observe the laws and regulations in force on hygiene and safety under his own responsibility. No responsibility is assumed for improper use.

Provide adequate training to personnel assigned to the use of chemical products.

Changes from the previous revision. Changes have been made to the following sections:

02/03/08/09/10/11/12/14/15.