



TECHNICAL DATA SHEET

TDS 04.019

Product

CEBOART STUCCO

Description

CEBOART STUCCO is a refined polished plaster for interiors, based on aged, filtered lime putty that grants a natural and perfect adhesion to the substrates, high water vapour permeability, resistance to moulds and bacteria and long-lasting stability. CEBOART STUCCO is very soft and pleasant to work with and it is therefore easy to reach the true and real effect of ancient Stucco Veneziano.

CEBOART STUCCO is available in 1 kg, 5 kg, 10 kg, 20 kg containers.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum plaster, lime or cement based fine renders. Carefully clean the surface and, if necessary, repair and level the substrate. Apply with a short pile roller or by brush one coat of CEBOFIX R, acrylic fixative, diluted with 20-30% water. In case of substrates which are highly irregular, it is advisable to apply one coat of CEBOFONDO, base coat, with a stainless steel trowel, in the same colour of CEBOART STUCCO.

Colouring

CEBOART STUCCO can be coloured with CeboColorStation or with CeboKit universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour; it is advisable to use bases and colorants carrying the same lot number.

Application

Apply CEBOART STUCCO in three coats with a stainless steel trowel.

1st coat: on the prepared and dry surface apply a sufficient quantity of product to attain a uniform and smooth layer.

2nd coat: when the first coat is completely dry (after about 6-8 hours) apply the second coat with a stainless steel trowel or blade to create the desired decoration, then smooth the surface perfectly.

3rd coat: apply a small quantity of product, slightly softened, and remove the excess; before the product dries completely, polish the entire surface with the same trowel.

Useful suggestions

When CEBOART STUCCO is thoroughly dry (minimum 24 hours), apply a coat of ECOCERA to increase the natural brightness of the plaster and to give water repellence to the surface.

Refer to the relative Technical Data Sheet for more details.

VOC Classification (2004/42/CE Directive)

Product not included in the annex
CEBOART STUCCO contains: 21g/l VOC

Technical characteristics

Estimated Coverage: 2 m²/kg

Appearance: dense paste

Specific weight: 1.59 g/cm³

pH: >10

Drying time: 6-8 hours between coats. Complete drying after about 24 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOART STUCCO is a lime based product and it is therefore strongly alkaline. Use suitable eye protections. In case of contact wash with plenty of water for at least 15 minutes. If irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.