



# TECHNICAL DATA SHEET

TDS 04.007

## Product

## CEBOSI SETOSO

## Description

CEBOSI SETOSO is an acrylic, water based, washable finish for interiors with subdued silk reflections and soft to the touch. It is the ideal product to create refined and essential decorative effects, with velvety shades and discreet plays of light, suitable for classic and modern interior design. The aesthetic value of the product combines with its excellent characteristics of resistance to washing, elasticity and lastingness.

CEBOSI SETOSO is available in 1 litre, 3 litres and 5 litres containers.

## Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render as long as properly treated. In case of rough or fine plastered walls, it is important to level out the surface with a suitable levelling paste.

Ensure that the substrates are perfectly clean, dry and uniform. In case of new or recently repaired walls, highly absorbent or chalky substrates, carefully clean the surface and apply a coat of priming fixative CEBOFIX M, by paintbrush, diluted 1:1 with water.

## Colouring

CEBOSI SETOSO can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

## Application

Apply CEBOSI SETOSO on the surface previously prepared with CEBOSI FONDO, in the same colour chosen for the finish.

CEBOSI SETOSO can be diluted up to 5% with water and applied with a short pile roller, in one or two coats to reach a perfect cover of the surface. Apply CeboSi Setoso when CeboSi Fondo is perfectly dry (6-8 hours).

According to the decoration desired, CEBOSI SETOSO can be applied by bush or by plastic trowel.

### Application by trowel:

With a sufficient quantity of product, apply a uniform layer of CEBOSI SETOSO, without dilution, using a plastic trowel and covering 2-3 square meters; go over the surface with the clean trowel to remove the excess of product. When the first coat is completely dry (after about 4-6 hours), apply the second coat with the same technique; go over the surface again with the clean trowel, being careful not to follow the same directions of the previous application, in order to create the desired chiaroscuro effect.

*Approximate coverage: 4 m<sup>2</sup>/l*

### Application by brush

Apply CEBOSI SETOSO diluted 25-30% with water, in two coats, with the appropriate CeboSi brush, available in 2½ and 4 inches size; dip the brush into the product and apply to the surface in crossed brush-strokes avoiding clear-cut squaring. When the first coat is completely dry (after about 4-6 hours), apply the second coat with the same technique.

*Approximate coverage: 8 m<sup>2</sup>/l*

## Protection

It is possible to use CEBOTATTO, transparent finish for interior, to obtain a pleasant tactile feeling combined with a deeply matt appearance. Additionally CEBOTATTO gives a greater brightness to the colours and an excellent scratch resistance to the surface.

## VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)  
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.  
CEBOSI SETOSO contains: 18 g/l VOC



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Review n.1  
Date: 01/03/2011

## TECHNICAL DATA SHEET

TDS 04.007

### Technical characteristics

Estimated Coverage: 4 – 8 m<sup>2</sup>/litre, in two coats, according to the method of application and type of finish chosen.  
Appearance: liquid  
Specific weight: 1.08 g/cm<sup>3</sup>  
pH: 8 – 9  
Resistance to washing: The product withstands ordinary cleaning maintenance.  
Drying time: 4-6 hours between coats. Thoroughly dry after 8-12 hours, according to ambient temperature and relative humidity.

### Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

### Safety warnings

CEBOSI SETOSO does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

---

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.