



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Review n.1  
Date: 06/07/2017

## TECHNICAL DATA SHEET

TDS 06.007

### Product

### CEBOVITRA PIU'

### Description

CEBOVITRA PIU' is a transparent, gloss protective product based on polyurethane resins.

CEBOVITRA PIU' is available in 1 litre and 2.5 litres cans.

### Surface treatment of the substrate

CEBOVITRA PIU' can be applied over all the substrates painted with acrylic based Cebos products.

### Colouring

CEBOVITRA PIU' shall not be coloured.

### Application

CEBOVITRA is ready-to-use and it must be applied by brush or short hair roller in one or two coats.

### Useful suggestions

### VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)  
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.  
CEBOVITRA PIU' contains: 25 g/l VOC

### Technical characteristics

Estimated Coverage: 12-14 m<sup>2</sup>/litre per coat.  
Appearance: liquid  
Specific weight: 1.05 g/cm<sup>3</sup>  
pH: 8.5 – 9  
Resistance to washing: highly resistant  
Drying time: 4-6 hours according to ambient temperature and relative humidity.

### Storage

Store the product in its original cans, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

### Safety warnings

CEBOVITRA PIU' requires specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.