

CLASSIC GRUND



Pigmented, water-based, interior wall primer

USE

For all indoor wall supports

PROPERTY'

- Excellent insulating power and uniformity of the absorption of the supports
- Promotes adhesion and coverage of finishes
- Colorable
- Opaque

CHARACTERISTICS

Composition: based on acrylic resins in aqueous emulsion. **Density:** approx. 1.36 kg/l **Physical parameters according to EN 13300:**

- | | | |
|-----------------------|----------|-----------------------------|
| - Granulometry | S1end | (< 100µm) |
| - I wait | G3opaque | (< 10 GU 85°) (approx. 2.5) |

EU limit value for VOC content: Cat. A/g: 30 g/l (2010).

This product contains a maximum of 30 g/l VOC.

Colors: White = DU1 base and shades available on colorimetric machine

Packaging: 2.5 – 12.5 l

Conservation: Store the product in its original packaging, tightly closed and in a dry, cool place, away from frost.

INSTALLATION

Application: by brush, roller and spray (airless).

Dilution: about 10-20% with water.

Conditions of application: Application and drying must take place in temperature conditions between +5°C and +30°C and with relative humidity lower than 85%

Theoretical consumption: from 90-110 ml/m² by hand.

Practical yield: about 9-11 m²/l. Yield may vary depending on the roughness, porosity and absorption characteristics of the substrates.

Drying (at 23°C and 50% RH):

- Dry to touch: 1-2 hours
- Repaintable: after 6 hours with Classic Grund
after 12 hours with another product

APPLICATION SYSTEMS

The application system and preparation of the substrates must be evaluated and chosen based on the current state and the conditions to which the substrate itself will be exposed.

Supports: the substrates must be healthy, clean, dry and free from saline efflorescence, mold, algae or fungi. They must not be crumbling or have detached parts.

To clean surfaces contaminated by microorganisms use Fungimos.

Preparation of the supports: clean the substrates and consolidate the crumbling ones. Repair the surface defects by applying suitable products from the Polyfilla Pro line. Do not apply the product on new plasters for at least 4 weeks.

New and highly absorbent surfaces:

- Apply Classic Grund with a brush/roller diluted with max 20% water.
- Once completely dry, complete the cycle with a suitable finish from the Herbol interior range.

CLASSIC GROUND

Irregular plasters, plasterboard and gypsum plasters: even out the surfaces by smoothing them with POLYFILLA PRO E200, wait until completely dry and sand to eliminate smudges and excess filler; apply as a base a coat of CLASSIC GRUND diluted to a maximum of 20% by volume with water, in the colour corresponding to the colour of the finish

Recommendations:

Classic Grund must be applied on perfectly dry, seasoned and compact substrates.

Do not apply on powdery surfaces or on poor levelling compounds, for which MULTIGRUND SB should be used as a base. Avoid applying the product on compact, closed-film, non-absorbent surfaces.

SECURITY INFORMATION

For information on the correct disposal, storage and handling of the product, please consult the relevant Safety Data Sheet.

All technical information contained herein is indicative. For further information, please consult our Technical Assistance service.

Herbalis is a trademark of: **AKZO
NOBEL COATINGS SpA SALES
OFFICE and**

ADMINISTRATIVE HEADQUARTERS:

Via Pietro Nenni, 14
28053 Castelletto Sopra Ticino (NO)
Tel. 0331 916611



www.herbol.it
customerservice@akzonobel.com

The effectiveness of our products and systems is based on years of practical experience and research conducted in our laboratories. We guarantee that the quality of work carried out with our products meets the suitability requirements set by Akzo Nobel Coatings SpA, provided that all instructions given by us are correctly followed and the work has been carried out in a skillful and professional manner. In the event that the final result has been adversely affected by circumstances beyond our control, any and all liability is expressly excluded and declined. The purchaser is responsible for checking whether the products delivered are suitable for the intended use. We reserve the right to change the content of this document without prior notice. As soon as a new version of this technical data sheet is available, it will no longer be valid.