

## MULTIGRUND SB



**Base product based on acrylic resins in solvent solution**

### USE

Solvent-based insulating and consolidating primer, covering for internal and external wall surfaces.

### PROPERTY

- Good insulating and consolidating power.
- Also effective for isolating nicotine stains, humidity, soot, ...
- Ideal for facades with residues of old paint or that have undergone a stripping process.
- Good covering power.
- Easy application.

### CHARACTERISTICS

**Composition:** based on finely ground synthetic resins, pigments and selected fillers. **Density:** approx. 1,340 kg/l

**EU limit value for VOC content:** Cat. A/h: 750 g/l 2010. This product contains a maximum of 500 g/l VOC.

**Colors:** white, can be colored in pastel shades with Acomix pastes.

**Packaging:** 10 l

**Conservation:** Store the product in its original packaging, tightly closed and in a dry, cool place, away from frost.

### INSTALLATION

**Application:** by brush and roller. (Do not spray; use only natural bristle brushes or wool rollers).

**Dilution:** ready to use.

**Conditions of application:** Application and drying must take place in temperature conditions between +5°C and +30°C and with relative humidity lower than 85%

**Theoretical consumption:** approx. 180 - 300 ml/m<sup>2</sup> by hand.

**Practical yield:** about 5 - 8 m<sup>2</sup>/l per coat. Yield may vary depending on the roughness, porosity and absorption characteristics of the substrates and the application system used.

**Cleaning the tools:** Sikkens Thinner L or white spirit.

**Drying (at 23°C and 50% RH):**

- Dust dry: after approximately 6 hours.
- Recoatable: after approximately 24 hours.

### APPLICATION SYSTEMS

The application system and preparation of the substrates must be evaluated and chosen based on the current state and the conditions to which the substrate itself will be exposed.

**Supports:** the substrates must be healthy, clean, dry and free from saline efflorescence, mold, algae or fungi. They must not be crumbling or have detached parts.

To clean surfaces contaminated by microorganisms use Fungimos. Do not apply the product on new plasters for at least 4 weeks.

**New and highly absorbent surfaces:**

- Apply a coat of Multigrund SB.
- Once completely dry, finish the cycle with a suitable finish from the Herbol range.

**Already painted surfaces:** clean the substrate thoroughly by high pressure washing; any saline efflorescence, mould, algae or fungi must be removed beforehand and adequately treated with Fungimos.

- Apply a coat of Multigrund SB.
- Once completely dry, finish the cycle with a suitable finish from the Herbol range.

## MULTIGRUND SB

### Recommendations:

- Avoid applying the product on compact, closed-film, non-absorbent surfaces. Do
- not apply on polystyrene insulating panels.
- It is recommended to use shade cloths on the scaffolding to protect from the sun's rays and any rain.

### SECURITY INFORMATION

For information on the correct disposal, storage and handling of the product, please consult the relevant Safety Data Sheet.

All technical information contained herein is indicative. For further information, please consult our Technical Assistance service.

**Herbalis** is a trademark of: **AKZO  
NOBEL COATINGS SpA SALES  
OFFICE and**

#### ADMINISTRATIVE HEADQUARTERS:

Via Pietro Nenni, 14  
28053 Castelletto Sopra Ticino (NO)  
Tel. 0331 916611



[www.herbol.it](http://www.herbol.it)  
[customerservice@akzonobel.com](mailto:customerservice@akzonobel.com)

The effectiveness of our products and systems is based on years of practical experience and research conducted in our laboratories. We guarantee that the quality of work carried out with our products meets the suitability requirements set by Akzo Nobel Coatings SpA, provided that all instructions given by us are correctly followed and the work has been carried out in a skillful and professional manner. In the event that the final result has been adversely affected by circumstances beyond our control, any and all liability is expressly excluded and declined. The purchaser is responsible for checking whether the products delivered are suitable for the intended use. We reserve the right to change the content of this document without prior notice. As soon as a new version of this technical data sheet is available, it will no longer be valid.