

RAPID INNER WHITE



Washable water-based wall paint with high covering power

USE

Interior walls and ceilings (ceilings, plaster, brickwork, particularly suitable for new plasterboard surfaces...)

Matte finish coat.

PROPERTY

- ELF quality (Emissions-und Lösemittelfrei): without plasticizers, without solvents and low emissions (the ELF label is awarded to paints that contain a reduced solvent content or are free of solvents).
- Easy to apply.
- Excellent covering power.
- Excellent white point.
- TÜV hygiene certificate: absence of harmful substances (heavy metals, organic compounds, plasticizers) during and after application.
- **Complies with Eurofins Indoor Air Comfort Gold (IAC Gold) indoor emissions test**
- **Compliant with CAM Edilizia requirements (DM 23 June 2022, n°256)**

CHARACTERISTICS

Composition: based on synthetic resins in aqueous emulsion, pigments and selected fillers. **Density:** approx.

1,490 kg/l **Physical parameters according to EN 13300:**

▪ Wet abrasion	class 2	(≥ 5 -m < 20 -m 200 cycles)
▪ Covering power	class 1 (with a yield of approximately 7 m ² /l) S	(> 99.5%)
▪ Granulometry	1end	(< 100 -m)
▪ I wait	G3opaque	(< 10 GU 85°) (approx. 1.5)

EU limit value for VOC content: Cat. A/a: 30 g/l 2010. This product contains a maximum of 1 g/l VOC.

Colors: white.

Packaging: 5 and 12.5 l.

Conservation: Store the product in its original packaging, tightly closed and in a dry, cool place, away from frost.

INSTALLATION

Application: by brush, roller and spray (also airless: pressure: approx. 190 bar - nozzle: starting from 0.017 inch - filter 30 - 60 mesh - angle 40° - 80°).

Dilution: 20 to 40% by volume with water.

Conditions of application: Application and drying must take place in temperature conditions between +5°C and +30°C and with relative humidity lower than 85%

Theoretical consumption: about 130 - 150 ml/m² by hand.

Practical yield: about 12 - 14 m²/l per coat. Yield may vary depending on the roughness, porosity and absorption characteristics of the substrates and the application system used.

Drying (at 23°C and 50% RH):

- Repaintable: after approximately 4 - 5 hours.
- Final drying: after approximately 2 or 3 days.

APPLICATION SYSTEMS

The application system and preparation of the substrates must be evaluated and chosen based on the state and conditions to which the substrate itself will be exposed.

Supports: the substrates must be healthy, clean, dry and free from saline efflorescence, mold, algae or fungi. They must not be crumbling or have detached parts.

To clean surfaces contaminated by microorganisms use Fungimos.

RAPID INNER WHITE

Preparation of the supports: do not clean the supports and consolidate the crumbling ones. Repair the surface defects by applying suitable products from the Polyfilla Pro line. Do not apply the product on new plasters for at least 4 weeks. In the case of patched surfaces for which it is necessary to even out the surface texture, it is possible to apply a coat of Fassaden Putzfüller following the instructions given in the respective Technical Data Sheet.

New and highly absorbent surfaces:

- Apply by brush, as a preparatory coat, one coat of Rapid Innenweiss diluted 50% by volume with water.
- Finally, apply two coats of Rapid Innenweiss diluted 20 to 40% by volume with water depending on the application system used.

Surfaces already painted with washable or breathable finishes:

- Apply directly two coats of Rapid Innenweiss diluted 20 to 40% by volume with water depending on the application system used.

Recommendations:

- The product is available exclusively in the “White” version. Therefore, coloring it with any type of pigment is not recommended.
- For some types of plasterboard panels, with specific characteristics and compositions, for example anti-humidity, fireproof, high density panels, etc. it is recommended to carry out a preliminary sampling of the cycle to verify the optimal adhesion to the substrate.

SECURITY INFORMATION

For information on the correct disposal, storage and handling of the product, please consult the relevant Safety Data Sheet.

All technical information contained herein is indicative. For further information, please consult our Technical Assistance service.

Herbalis is a trademark of: **AKZO NOBEL COATINGS SpA SALES OFFICE and**

ADMINISTRATIVE HEADQUARTERS:

Via Pietro Nenni, 14
28053 Castelletto Sopra Ticino (NO)
Tel. 0331 916611



www.herbol.it
customerservice@akzonobel.com

The effectiveness of our products and systems is based on years of practical experience and research conducted in our laboratories. We guarantee that the quality of work carried out with our products meets the suitability requirements set by Akzo Nobel Coatings SpA, provided that all instructions given by us are correctly followed and the work has been carried out in a skillful and professional manner. In the event that the final result has been adversely affected by circumstances beyond our control, any and all liability is expressly excluded and declined. The purchaser is responsible for checking whether the products delivered are suitable for the intended use. We reserve the right to change the content of this document without prior notice. As soon as a new version of this technical data sheet is available, it will no longer be valid.