# **Safety Data Sheet**

## SECTION 1. Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier Code:

193.10

Name Hydromatt Plus

1.2. Relevant identified uses of the substance or mixture and uses advised against

Description / Use Super matt washable water-based paint

1.3. Information on the supplier of the safety data sheet

Business name DI MAIO COLORI SRL

Address Via Madonna delle Grazie - Industrial area

Location and State 80030 Castello di Cisterna (NA)

Italy

tel. 081-8038645 fax 081-5213370

e-mail of the competent person

1.4. Emergency telephone number

For urgent information contact Di Maio Colori srl

Tel. +39 081 8038645 fax +39 081 5213370 hours of the poison control center AORNA Cardarelli Naples

Tel. +39 081 7472870 - 081 5753333 fax +39 081 7472868 Availability 24 h

## **SECTION 2. Hazards identification**

# 2.1. Substance or mixture classification

The product is not classified as dangerous according to the provisions of Regulation (EC) 1272/2008 (CLP).
However, since the product contains dangerous substances in a concentration such as to be declared in section 3, it requires a safety data sheet with adequate information, in compliance with Regulation (EU) 2015/830.
Hazard classification and indications:

## 2.2. Label elements

Danger labeling pursuant to Regulation (EC) 1272/2008 (CLP) and subsequent amendments and adjustments.

Hazard pictograms:



193.10 - Hydromatt Plus

Revision n. 2

Revision date 18/12/2017

New issue

Printed on 10/04/2020

Page no. 2/15

Warnings: --

Hazard statements:

**EUH210** Safety data sheet available on request.

EUH208 Contains:, Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-

one May produce an allergic reaction.

Precautionary advice:

- -

### 2.3. Other dangers

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

# **SECTION 3. Composition / information on ingredients**

#### 3.1. Substances

Not relevant information

### 3.2. Blends

Contains:

Identification x = Conc.% Classification 1272/2008 (CLP)

Monoethylene glycol

CAS 107-21-1 1.5 ≤ x <2 Acute Tox. 4 H302, STOT RE 2 H373

THERE IS 203-473-3

INDEX 603-027-00-1

Reg. No. 01-2119456816-28

Mixture of: 5-chloro-2methyl-2Hisothiazol-3-one; 2-

 methyl-2Hisothiazol-3-one

 CAS
 55965-84-9
 0 ≤ x <0.0015</td>
 Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, Skin Corr. 1B

H314, Skin Sens. 1 H317, Aquatic Acute 1 H400 M = 1, Aquatic Chronic 1

H410 M = 1

THERE IS

INDEX 613-167-00-5

The full wording of the hazard statements (H) is given in section 16 of the sheet.

## **SECTION 4. First aid measures**

## 4.1. Description of first aid measures

EYES: Remove any contact lenses. Wash immediately and abundantly with water for at least 30/60 minutes, opening the eyelids well. Consult a physician immediately.

SKIN: Take off contaminated clothing. Take a shower immediately. Consult a physician immediately.



INGESTION: Give as much water to drink as possible. Consult a physician immediately. Do not induce vomiting unless expressly authorized by your doctor.

INHALATION: Call a doctor immediately. Take the person out into the fresh air, away from the scene of the accident. If breathing stops, give artificial respiration. Take adequate precautions for the rescuer.

#### 4.2. Most important symptoms and effects, both acute and delayed

No specific information on symptoms and effects caused by the product is known.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## **SECTION 5. Firefighting measures**

### 5.1. Fire fighting

SUITABLE EXTINGUISHING MEDIA

Extinguishing media are: carbon dioxide, foam, chemical powder. For product leaks and spills that have not caught fire, water spray can be used to disperse flammable vapors and protect those involved in stopping the leak.

UNSUITABLE EXTINGUISHING MEDIA

Do not use water jets. Water is not effective to extinguish the fire, however it can be used to cool closed containers exposed to the flame, preventing bursts and explosions.

### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Overpressure can be created in containers exposed to fire with danger of explosion. Avoid breathing combustion products.

### 5.3. Recommendations for firefighters

## GENERAL INFORMATIONS

Cool the containers with jets of water to avoid product decomposition and the development of substances potentially hazardous to health. Always wear full fire protection equipment. Collect the extinguishing water which must not be discharged into the sewers. Dispose of the contaminated water used for extinguishing and the residue of the fire according to current regulations.

Normal clothing for firefighting, such as an open circuit compressed air breathing apparatus (EN 137), flame retardant suit (EN469), flame retardant gloves (EN 659) and fire brigade boots (HO A29 or A30).

## **SECTION 6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop the leak if there is no danger.

Wear suitable protective equipment (including personal protective equipment referred to in section 8 of the safety data sheet) to prevent contamination of skin, eyes and personal clothing. These indications are valid both for the workers and for emergency interventions.

### 6.2. Environmental precautions

Prevent the product from entering sewers, surface water, groundwater.

## 6.3. Methods and materials for containment and cleaning up



Suck up the leaked product into a suitable container. Evaluate the compatibility of the container to be used with the product, checking section 10. Absorb the remainder with inert absorbent material.

Provide sufficient ventilation of the place affected by the leak. The disposal of contaminated material must be carried out in accordance with the provisions of point 13.

#### 6.4. Reference to other sections

Any information regarding personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage**

### 7.1. Precautions for Safe Handling

Keep away from heat, sparks and open flames, do not smoke or use matches or lighters. Vapors can ignite with explosion, therefore accumulation must be avoided by keeping doors and windows open and ensuring cross ventilation. Without adequate ventilation, vapors can accumulate on the ground and catch fire even at a distance, if triggered, with the risk of backfire. Avoid the accumulation of electrostatic charges. Connect to an earth socket in the case of large packages during the transfer operations and wear antistatic shoes. The strong agitation and the vigorous flow of the liquid in the pipes and equipment can cause the formation and accumulation of electrostatic charges. To avoid the danger of fire and explosion, never use compressed air for handling. Open containers carefully, as they may be under pressure. Do not eat, drink or smoke during use. Avoid the dispersion of the product in the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep only in the original container. Keep the containers closed, in a well-ventilated place, away from direct sunlight. Store in a cool and well-ventilated place, away from heat sources, open flames, sparks and other sources of ignition. Keep containers away from any incompatible materials, checking section 10.

## 7.3. Specific end uses

Information not available

## **SECTION 8. Exposure controls / personal protection**

### 8.1. Control parameters

Normative requirements:

EU OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161 / EU; Directive 2006/15 / EC; Directive

2004/37 / EC; Directive 2000/39 / EC; Directive 91/322 / EEC.

TLV-ACGIH ACGIH 2019

Monoethylene glyco	l					
Threshold limit value						
Guy	State	TWA / 8h	TWA / 8h STEL / 15min			
		mg / m3	ppm	mg / m3	ppm	
OEL	EU	52	20	104	40	
TLV-ACGIH		52	20	100	40	A4, C, Skin
Predicted No Effect Concen	tration on the Environme	ent - PNEC				
Reference value in fresh v	water			10	mg / l	
Reference value in sea wa	ater			1	mg / l	



Reference value for sediments in fresh water

Reference value for STP microorganisms

### **DI MAIO COLORI SRL**

Revision n. 2

Revision date 18/12/2017

Printed on 10/04/2020

New issue

Page no. 5/15

# 193.10 - Hydromatt Plus

3.7

199 5

37	mg / kg	

mg/kg

mg/I

Reference value for the terrestrial compartment 1.53 mg / kg

Health - Derived no-effec	t level - DNEL / D	MEL						
	Effects on				Effects on			
	consumers				workers			
Route of Exposition	Acute premises	Acute systemic	Chronic local	Systemic			Systemic	Systemic
				chronic			acute	chronic
Inhalation			7 mg / m3	VND	35 mg / m3	VND		
Dermal			53 mg / kg / d	VND			106 mg / kg / d	VND

Legend:

(C) = CEILING; INALAB = Inhalable Fraction; RESPIR = Breathing Fraction; TORAC = Thoracic Fraction.

VND = hazard identified but no DNEL / PNEC available; NEA = no exposure expected; NPI = no hazard identified.

### 8.2. Exposure controls

Considering that the use of adequate technical measures should always take priority over personal protective equipment, ensure good ventilation in the workplace through effective local exhaust.

For the choice of personal protective equipment, if necessary, seek advice from your chemical suppliers. Personal protective equipment must bear the CE mark which certifies their compliance with current regulations.

### HAND PROTECTION

Protect hands with category III work gloves (ref. Standard EN 374).

For the final choice of the material of the work gloves it is necessary to consider: compatibility, degradation, breakage time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as it is not foreseeable. Gloves have a wear time that depends on the duration and mode of use.

## SKIN PROTECTION

Wear category I work clothes with long sleeves and safety footwear for professional use (ref. Regulation 2016/425 and standard EN ISO 20344). Wash with soap and water after removing protective clothing.

## EYE PROTECTION

It is recommended to wear airtight protective goggles (ref. Standard EN 166).

### RESPIRATORY PROTECTION

In case of exceeding the threshold value (eg TLV-TWA) of the substance or of one or more of the substances present in the product, it is recommended to wear a mask with a type B filter whose class (1, 2 or 3) must be chosen in relation to the limit concentration of use. (ref. standard EN 14387). If there are gases or vapors of a different nature and / or gases or vapors with particles (aerosols, fumes, mists, etc.), combined filters must be provided. The use of respiratory protection means is necessary if the technical measures adopted are not sufficient to limit the exposure of the worker to the threshold values taken into consideration. The protection offered by the masks is however limited.

In the event that the substance in question is odorless or its olfactory threshold is higher than the relative TLV-TWA and in the event of an emergency, wear an opencircuit compressed air breathing apparatus (ref. Standard EN 137) or a self-contained breathing apparatus. outdoor air (ref. EN 138 standard). For the correct choice of the respiratory protection device, refer to the EN 529 standard.

## ENVIRONMENTAL EXPOSURE CONTROLS

Emissions from manufacturing processes, including those from ventilation equipment should be controlled for compliance with environmental protection legislation.

## **SECTION 9. Physical and chemical properties**



193.10 - Hydromatt Plus

Revision n. 2

Revision date 18/12/2017

Printed on 10/04/2020

Page no. 6/15

### 9.1. Information on basic physical and chemical properties

pasty liquid Physical state Color White

Odor characteristic Odor threshold Unavailable 8 - 9 рΗ

Melting or freezing point Initial Unavailable 100 ° C boiling point Boiling range Flash Unavailable point Evaporation rate Unavailable

Unavailable

Flammability of solids and Unavailable gases Lower flammability limit Unavailable Upper flammability limit Lower Unavailable explosive limit Upper explosive Unavailable limit Vapor pressure Unavailable

Unavailable

Vapor density Unavailable Relative density Unavailable soluble in water Solubility Partition coefficient: n-octanol / water Auto-Unavailable Unavailable ignition temperature Unavailable Decomposition temperature 3000 - 4500 cP Viscosity

none **Explosive properties** Oxidizing properties none

### 9.2. Other information

Information not available

# **SECTION 10. Stability and reactivity**

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable under normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

In normal conditions of use and storage no dangerous reactions are foreseeable.



### 10.4. Conditions to avoid

None in particular. However, follow the usual precautions towards chemicals.

## 10.5. Incompatible materials

Information not available

### 10.6. Hazardous decomposition products

Information not available

# **SECTION 11. Toxicological information**

In the absence of experimental toxicological data on the product itself, any health hazards of the product have been assessed on the basis of the properties of the substances contained, according to the criteria established by the reference legislation for classification.

Therefore, consider the concentration of the individual dangerous substances possibly mentioned in sect. 3, to evaluate the toxicological effects deriving from exposure to the product.

### 11.1. Information on toxicological effects

Metabolism, kinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects and chronic effects from short and long term exposure

Information not available

Interactive effects

Information not available

## **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture:
Not classified (no relevant component) LD50
(Oral) of the mixture:
> 2000 mg / kg
LD50 (Dermal) of the mixture:
Not classified (no relevant component)

Calcium Carbonate

LD50 (Oral)> 5000 mg / kg Rat



Revision n. 2

Revision date 18/12/2017

w issue

Printed on 10/04/2020

Page no. 8/15

# 193.10 - Hydromatt Plus

sodium and magnesium aluminosilicate

LD50 (Oral)> 2000 mg / kg Rat GRACE - OECD 423

LD50 (Dermal)> 5000 mg / kg Rabbit - Comparable substance - OECD 402

LC50 (Inhalation)> 2080 mg / l / 4h Rat OECD 403

2,2,4 Trimethyl 1,3 pentanediol monoisobutyrate

LD50 (Oral)> 3200 mg / kg Rats

Monoethylene glycol

LD50 (Oral) 7712 mg / kg Rat

LD50 (Dermal)> 10600 mg / kg Rabbit

LC50 (Inhalation)> 2.5 mg / l / 4h

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one

LD50 (Oral) 550 mg / kg Rat

LD50 (Dermal) 1000 mg / kg Rat

LC50 (Inhalation) 0.31 mg / l / 4h Rat - Dusts and mists

titanium dioxide

LD50 (Oral)> 5000 mg / kg

LC50 (Inhalation)> 6.82 mg / l / 4h rat

kaolin, calcined

LD50 (Oral)> 20000 mg / kg Rat

## SKIN CORROSION / SKIN IRRITATION

It does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / EYE IRRITATION



It does not meet the classification criteria for this hazard class

## RESPIRATORY OR SKIN SENSITIZATION

May produce an allergic reaction. Contains: Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one

### MUTAGENICITY ON GERMINAL CELLS

It does not meet the classification criteria for this hazard class

## CARCINOGENICITY

It does not meet the classification criteria for this hazard class

### REPRODUCTION TOXICITY

It does not meet the classification criteria for this hazard class

### SPECIFIC TARGET ORGAN TOXICITY (STOT) - SINGLE EXPOSURE

It does not meet the classification criteria for this hazard class

### SPECIFIC TARGET ORGAN TOXICITY (STOT) - REPEATED EXPOSURE

It does not meet the classification criteria for this hazard class

### DANGER IN CASE OF SUCTION

It does not meet the classification criteria for this hazard class

## **SECTION 12. Ecological information**

As specific data on the preparation are not available, use according to good working practices, avoiding to disperse the product in the environment. Avoid dispersing the product in the ground or water courses. Notify the competent authorities if the product has reached water courses or if it has contaminated the soil or vegetation. Take measures to minimize the effects on the aquifer.

## 12.1. Toxicity

Monoethylene glycol
Acute toxicity - Aquatic plants EC50 96
hours 6500 - 13000 mg / I Acute toxicity
- Microorganisms EC50 30, om 225 mg /
I Activated sludge
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one
Acute IC50 0.379 mg / I Pseudokirrchneriella subcapitata 72 hours

Calcium Carbonate

LC50 - Pisces

> 100000 mg / I / 96h Oncorhynchus mykiss (Rainbow trout)

EC50 - Crustaceans

> 1000 mg / l / 48h Daphnia magna

EC50 - Algae / Aquatic Plants

> 200 mg / l / 72h Desmodesmus subspicatus



193.10 - Hydromatt Plus

Revision n. 2

Revision date 18/12/2017

ew issue

Printed on 10/04/2020

Page no. 10/15

# sodium and magnesium

aluminosilicate LC50 - Fish 10000 mg / l / 96h Brachydanio rerio

EC50 - Crustaceans > 10000 mg / I / 48h Daphnia Magna 2500
EC50 - Algae / Aquatic Plants EC10 mg / I / 72h Scenedesmus subspicatus 41
Algae / Aquatic Plants Chronic mg / I / 72h Scenedesmus subspicatus 1000

NOEC Crustaceans mg / I 21 d (Daphnia magna)

### 2,2,4 Trimethyl 1,3 pentanediol

monoisobutyrate

LC50 - Pisces 30 mg / 1 / 96h

EC50 - Crustaceans > 95 mg / I / 48h Daphnia

### Monoethylene glycol

LC50 - Pisces 72860 mg / I / 96h Big-headed vairon
EC50 - Crustaceans > 100 mg / I / 48h Daphnia magna

### Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-

one; 2-methyl-2H-isothiazol-3-one

LC50 - Pisces 0.58 mg / l / 96h Danio rerio 1.02 EC50 - Crustaceans mg / l / 48h Daphnia magna

EC10 Algae / Aquatic Plants

0.188 mg / I / 72h Pseudokirchneriella subcapitata

NOEC Chronic Fish

0.098 mg / I Oncorhynchius mykiss (rainbow trout)

Chronic NOEC Crustaceans 0.004 mg / I Daphnia magna

Chronic NOEC for Algae / Aquatic Plants 0.0012 mg / I Pseudokirchneriella subcapitata

### titanium dioxide

LC50 - Pisces > 100 mg / l / 96h

EC50 - Crustaceans > 100 mg / I / 48h Daphnia

### kaolin, calcined

LC50 - Pisces > 100 mg / l / 96h Oncorhynchus mykiss

EC50 - Crustaceans > 1 mg / I / 48h Daphnia magna

EC50 - Algae / Aquatic Plants > 100 mg / l / 72h Scenedesmus subspicatus

### 12.2. Persistence and degradability

Monoethylene glycol

Rapidly degradable Degradation (90%)> 10 days

## 12.3. Bioaccumulation potential

## Monoethylene glycol

Partition coefficient - 1.36

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one LogPow



- 0.486 to 0.401

Monoethylene glycol

Partition coefficient: n-octanol / water 1.36

12.4. Mobility in soil

Monoethylene glycol Coefficient of adsorption / desorption Soil Koc 1

2,2,4 Trimethyl 1,3 pentanediol

monoisobutyrate

Partition coefficient: soil / water 300

Monoethylene glycol

Partition coefficient: soil / water 1 estimated

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain PBT or vPvB substances in percentage greater than 0.1%.

### 12.6. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

### 13.1. Waste treatment methods

Reuse if possible. The residues of the product as such are to be considered special non-hazardous waste.

Disposal must be entrusted to an authorized waste management company, in compliance with national and possibly local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be sent for recovery or disposal in compliance with national waste management regulations.

# **SECTION 14. Transport information**


The product is not to be considered dangerous pursuant to the provisions in force on the transport of dangerous goods by road (ADR), by rail (RID), by sea (IMDG Code) and by air (IATA).

### 14.1. UN number

Not applicable

## 14.2. UN proper shipping name

& Dimā	DI MAIO COLORI SRL	Revision n. 2			
		Revision date 18/12/2017			
		New issue			
	193.10 - Hydromatt Plus	Printed on 10/04/2020			
	193.10 - Hydromatt Flus	Page no. 12/15			
Not applicable					
14.3. Transport hazard classes					
Not applicable					
14.4. Packing group					
Not applicable					
14.5. Environmental hazards					
Not applicable					
14.6. Special precautions for users					
Not applicable					
14.7. Transport in bulk according to	Annex II of MARPOL and the IBC Code				
Not relevant information					
SECTION 15. Regulatory information					
15.1. Health, safety and environme	ental legislation and regulations specific to the substance or mixture				
Seveso Category - Directive 2012/18 / E	EC: None				
Restrictions relating to the product or the	e substances contained according to Annex XVII Regulation (EC) 1907/2006				
None					
Substances in Candidate List (Art. 59 REAG	<u>CH)</u>				
	oes not contain SVHC substances in percentage greater than 0.1%.				
Substances subject to authorization (A	nnex XIV REACH)				
None					



Substances subject to export notification obligation Reg. (EC) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Sanitary checks

Information not available

### 15.2. Chemical safety assessment

A chemical safety assessment has not been developed for the mixture and the substances it contains.

## **SECTION 16. Other information**

Text of hazard (H) indications mentioned in sections 2-3 of the sheet:

Acute Tox. 3 Acute toxicity, category 3
Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2 Skin

Skin Corr. 1Bcorrosion, category 1BSkin Sens. 1Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

**H301** Toxic if swallowed.

**H311** Toxic in contact with the skin.

H331 Toxic if inhaled.H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure. It

H314 causes serious skin burns and serious eye injuries.H317 May cause an allergic skin reaction. Very toxic

**H400** to aquatic organisms.

**H410** Very toxic to aquatic life with long lasting effects. Safety data sheet

**EUH210** available on request.

## LEGEND:

- ADR: European agreement for the transport of dangerous goods by road
- CAS NUMBER: Number of the Chemical Abstract Service
- EC50: Concentration affecting 50% of the population under test
- CE NUMBER: Identification number in ESIS (European archive of existing substances)



- CLP: EC Regulation 1272/2008
- DNEL: Derived no effect level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System for Classification and Labeling of Chemicals
- IATA DGR: Regulations for the transport of dangerous goods of the International Air Transport Association
- IC50: Concentration of immobilization of 50% of the population subject to testing
- IMDG: International maritime code for the transport of dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identification number in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- OEL: Occupational exposure level
- PBT: Persistent, bioaccumulating and toxic according to REACH
- PEC: Predicted environmental concentration
- PEL: Predictable level of exposure
- PNEC: Predicted No Effect Concentration
- REACH: EC Regulation 1907/2006
- RID: Regulations for the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration which must not be exceeded during any moment of occupational exposure.
- TWA STEL: Short term exposure limit
- TWA: Weighted average exposure limit
- VOC: Volatile organic compound
- vPvB: Very persistent and very bioaccumulating according to REACH
- WGK: Water hazard class (Germany).

### GENERAL BIBLIOGRAPHY:

- 1. Regulation (EC) 1907/2006 of the European Parliament (REACH)
- 2. Regulation (EC) 1272/2008 of the European Parliament (CLP)
- 3. Regulation (EU) 790/2009 of the European Parliament (I Atp. CLP)
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 of the European Parliament (II Atp. CLP)
- 6. Regulation (EU) 618/2012 of the European Parliament (III Atp. CLP)
- 7. Regulation (EU) 487/2013 of the European Parliament (IV Atp. CLP)
- 8. Regulation (EU) 944/2013 of the European Parliament (V Atp. CLP)
- 9. Regulation (EU) 605/2014 of the European Parliament (VI Atp. CLP) 10. Regulation (EÚ) 2015/1221 of the European Parliament (VII Atp. CLP)
- 11. Regulation (EU) 2016/918 of the European Parliament (VIII Atp. CLP)
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- NI Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA Agency website
- Database of SDS models of chemical substances Ministry of Health and National Institute of Health

## Note for the user:

The information contained in this sheet is based on the knowledge available to us at the date of the last version. The user must ensure the suitability and completeness of the information in relation to the specific use of the product.

This document should not be construed as a quarantee of any specific property of the product.

Since the use of the product does not fall under our direct control, the user is obliged to observe the laws and regulations in force regarding hygiene and safety under his own responsibility. No responsibility is assumed for improper use.

Provide adequate training for personnel involved in the use of chemical products.

The classification of the product is based on the calculation methods set out in Annex I of CLP, unless otherwise indicated in sections 11 and 12. The methods for assessing the physico-chemical properties are given in section 9.

Changes from the previous revision Changes were made to the following sections:

<b>&amp; Dima</b>	DI MAIO COLORI SRL	Revision n. 2
		Revision date 18/12/2017  New issue
	193.10 - Hydromatt Plus	Printed on 10/04/2020 Page no. 15/15

	193.10 - Hydromatt Plus	Printed on 10/04/2020
	155. 10 - Hydromater ids	Page no. 15/15
01/03/04/07/08/09/11/12/16.		