



FINGLASS

Vitrifying acrylic

Description	Glossy acrylic finish, the product gives a shine to all water-based paints or plastic coatings.
Composition	Based on acrylic resins in aqueous dispersion
Specific weight	1,000 kg / lt
Surrender	10 - 12 sqm / lt
Appearance of the film	Satin
Resistance to water	Great.
Resistance to chemical agents	Excellent for alkalis.
Resistance to agents atmospheric	Great.
storage	In tightly closed package
Use	Vitrifying agent for exteriors and interiors
Application	Brush or roller
Dilution	Ready to use
Temperature of application	10-35C ° relative humidity max. 85%
Color	Transparent
Pack of sale	0,750 lt - 5 lt
Cleaning tools	Waterfall

Preparation of the support

- Eliminate all traces of dust on the water-based paint.
- Apply a coat of FINGLASS according to the instructions above.

SPECIFICATION ITEM (for tenders and estimates)

Description	Glossy acrylic finish, the product gives a shine to all water-based paints or plastic coatings.
Specific weight	1,000 kg / lt

Warnings

- The substrate temperature must be at least 3C ° higher than the condensation temperature.
- Apply the product with temperatures ranging from 10C ° -35C ° and with a relative humidity of max. 85%
- If the product is applied in closed environments, continuous replacement is required air, so that the water vapors escape.
- Apply the product on a carefully treated surface.
- The yield may vary according to the characteristics of the substrate.
- Do not apply the product in direct sunlight.

The technical information contained in this sheet is the result of laboratory tests and practical experiences which do not involve any responsibility on our part, as the conditions of use are not under our direct control. In cases of doubt, it is always advisable to ask our technicians for further information regarding the correct application cycle.