




Alpha Grond

Product description

Pliolite pigmented primer for exterior and interior wall surfaces, solvent based.

Property

- ✓ Specific for the preparation of reinforced concrete surfaces cast on site and prefabricated.
- ✓ It guarantees optimal adhesion on slightly chalking substrates.
- ✓ Free of aromatic solvents.
- ✓ Unsaponifiable.
- ✓ Promotes uniformity of color and coverage of paints and coatings.

Main feature

- ✓ Consolidates and evens the absorption of supports

Technical features

Dry to the touch

Touch dry after 4-6 hours.

Overpaintable

Recoat after 12 h.

Surrender

8-10 m² / l per coat. The yield may vary according to the roughness, porosity and absorption characteristics of the substrates and the application system adopted.

General informations

Composition

Solvent based

Property

Specific for the preparation of cast-on-site and prefabricated reinforced concrete surfaces., Guarantees optimal adhesion on slightly chalking substrates., Free of aromatic solvents., Unsaponifiable., Promotes uniformity of color and coverage of paints and coatings.

Color range

5051 Color Concept, Alpha 501 for outdoors, Match Point 200

Packaging

5 l, 15 l

Application system

For detailed information and before using the product, please consult the relevant data sheet.

Method of application

By brush (on substrates with marked absorption and chalking), by roller or by spray.