



SAFETY DATA SHEET

ALPHALOXAN FLEX

SECTION 1: identification of the substance / mixture and of the company / undertaking

1.1. Product identifier Product

name :  ALPHALOXAN FLEX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Product :  Water-based paint for exteriors.

1.3. Information on the supplier of the safety data sheet

Akzo Nobel Coatings SpA Via
Pietro Nenni 14,
28053 Castelletto sopra Ticino,
Tel. +39 0331 916611
Internet: www.sikkens.it

E-mail address of the Responsible person of the safety data sheet : service.clienti@akzonobel.com

1.4 Emergency telephone number

Telephone number : Telephone number: +39 0331 916611 (active 24/7) International AkzoNobel emergency number: +31 71 3086944 (active 24/7)

Version : 20

Date of issue : 31-8-2020
previous one

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Blend

Classification according to EC Regulation No. 1272/2008 [CLP / GHS]

Aquatic Chronic 3, H412

This product is classified as dangerous according to Regulation (EC) 1272/2008 and subsequent amendments.

Ingredients of unknown toxicity : 0%

Ingredients of unknown ecotoxicity : 0%

See section 16 for the full text of the hazard statements mentioned above. For more detailed information on health effects and symptoms, see Section 11.

2.2 Label elements

Warning : No warnings.

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Date of issue / Date of revision : 11-3-2021

Page: 1/17

ALPHALOXAN FLEX**SECTION 2: Hazards identification****Precautionary advice****General**

- : P102 - Keep out of reach of children.
 P101 - If a doctor is consulted, have the product container or label available.

Prevention

- : P262 - Avoid contact with eyes, skin or clothing.

Reaction

- : P312 - If you feel unwell, call a POISON CENTER or doctor. Not applicable.

storage

:

Disposal

- : P501 - Dispose of product and container in accordance with local, regional, national, international regulations.

Additional elements of the label

- : Contains 1,2-benzisothiazol-3 (2H) -one, C (M) IT / MIT (3: 1) and 2-octyl-2H-isothiazol-3-one. It can cause an allergic reaction.
 Attention! In case of vaporization, dangerous respirable droplets may be formed. Do not breathe vapors or mists.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain substances, preparations and articles dangerous

- : Not applicable.

Special Packaging Obligations**Containers that must be equipped with a child safety lock**

- : Not applicable.

Tactile warning of danger

- : Not applicable.

2.3 Other dangers**Other dangers not mentioned in the classification**

- : None known.

SECTION 3: Composition / information on ingredients**3.2 Mixtures**

:Blend

Product name/ ingredient	Identifiers	%	Regulation (EC) n. 1272/2008 [CLP]	Guy
diuron	CE: 206-354-4 CAS number: 330-54-1 Index: 006-015-00-9	≤0.1	Acute Tox. 4, H302 Carc. 2, H351 STOT RE 2, H373 Aquatic Acute 1, H400 (M = 10) Aquatic Chronic 1, H410 (M = 10)	[1]
1,2-benzisothiazol-3 (2H) -one	CE: 220-120-9 CAS number: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M = 1) Acute Tox. 4, H302	[1]
Octilinine (ISO)	CE: 247-761-7 CAS number: 26530-20-1	<0.05	Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M = 10) Aquatic Chronic 1, H410 (M = 10) Acute Tox. 3, H301	[1]
zinc pyrithione	CE: 236-671-3 CAS number: 13463-41-7	<0.1	Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360FD (Fertility and Unborn Child)	[1]

ALPHALOXAN FLEX

SECTION 3: Composition / information on ingredients

toluene	REACH #: 01-2119471310-51 CE: 203-625-9 CAS number: 108-88-3 Index: 601-021-00-3	≤0.1	STOT RE 1, H372 (oral) Aquatic Acute 1, H400 (M = 100) Aquatic Chronic 1, H410 (M = 1) Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d (Unborn child) STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	[1] [2]
C (M) IT / MIT (3: 1)	REACH #: 01-2120764691-48 CAS number: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M = 100) Aquatic Chronic 1, H410 (M = 100) Flam. Liq. 2, H225	[1]
methanol	CE: 200-659-6 CAS number: 67-56-1 Index: 603-001-00-X	<0.1	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 See section 16 for the full text of the danger mentioned above.	[1] [2]

There are no additional ingredients which, in the current knowledge of the supplier and in the applicable concentrations, are classified as dangerous for health or the environment, meet the PBT or vPvB criteria or are considered as substances with an equivalent degree of problematicity or substances to which an occupational exposure limit has been assigned and should therefore be reported in this section.

Guy

[1] Substance presenting a health or environmental hazard

[2] Substance for which there are workplace exposure limits

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional information related to company policy

Occupational exposure limits, if known, are listed in section 8.

SECTION 4: first aid measures

4.1 Description of first aid measures General

- : If in doubt or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If the victim is unconscious, have him assume the safety position and call the doctor.

Eye contact

- : Remove contact lenses, rinse thoroughly with clean, fresh water, holding the eyelids open for at least 10 minutes and seek immediate medical attention.

By inhalation

- : Bring to fresh air. Keep the person warm and at rest. In case of lack of breathing, irregular breathing or respiratory arrest, give artificial respiration or have oxygen administered by trained personnel.

Skin contact

- : Remove contaminated clothing and shoes. Wash thoroughly with soap and water or use an effective skin cleanser. DO NOT use solvents or thinners.

Ingestion

- : If swallowed, seek medical advice immediately and show the container or label. Keep the person warm and at rest. DO NOT induce vomiting.

ALPHALOXAN FLEX**SECTION 4: first aid measures**

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. Performing mouth-to-mouth resuscitation can be dangerous for the person helping.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture was evaluated following the conventional method of the CLP regulation (EC) No. 1272/2008 and is consequently classified according to its toxicological properties. For more details, see Sections 2 and 3.

Exposure to solvent vapor concentrations above the pre-established occupational limit can be harmful to health, causing irritation of the mucous membranes and respiratory tract with adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, dizziness and wobbling, fatigue, muscle weakness, sleepiness and in extreme cases loss of consciousness.

Solvents may cause some of the aforementioned effects via skin absorption. Repeated or prolonged contact with the mixture can result in the removal of natural skin fat, resulting in non-allergic contact dermatitis and absorption through the skin.

Contact of the liquid with the eyes can cause irritation and reversible damage.

Ingestion can cause nausea, diarrhea and vomiting.

If known, the delayed and immediate effects, as well as the chronic effects of the components deriving from short and long-term exposure, by the oral and dermal route, by inhalation and by contact with the eyes, are taken into account.

Contains 1,2-benzisothiazol-3 (2H) -one, 2-octyl-2H-isothiazol-3-one, C (M) IT / MIT (3: 1). It can cause an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed Notes to physician

: Treat symptomatically. If large quantities are ingested or inhaled, contact a poison control center immediately.

Specific treatments : No specific treatment.

See Section 11 for Toxicological Information (Section 11)

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media :Recommended: alcohol resistant foam,CO₂,powders, water spray.

Unsuitable extinguishing media :Do not use full jet water.

5.2 Special hazards arising from the substance or mixture

Hazards arising from the substance or mixture : Any fires develop thick black smoke. Exposure to decomposition products can be dangerous to health.

Hazardous Combustion Products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, nitrogen oxides.

5.3 Recommendations for firefighters

Special actions of protection for firefighters : Cool closed containers exposed to flames with water. Do not channel the products of a fire into drains or water courses.

Special protective equipment for personnel fire fighting : The use of a self-contained breathing apparatus may be required.

ALPHALOXAN FLEX

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For those who do not intervene directly : Remove any sources of ignition and ventilate the room. Avoid breathing vapors or mists. Consult the protective measures listed in sections 7 and 8.

For those who intervene directly : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency service operators".

6.2 Environmental precautions: Do not dispose of the product in the sewer system and water courses. In case of contamination by the product of lakes, rivers or waste water, inform the competent authorities in accordance with current legislation.

6.3 Methods and materials for: containment and Contain and collect any spills with non-combustible absorbent material, such as sand, earth, vermiculite, diatomite and dispose of the product in a container in accordance with current legislation (see Section 13). Clean, preferably using a detergent. Avoid using solvents.

quenching and tempering

6.4 Reference to other sections : For emergency telephone numbers, see Section 1.
See Section 8 for information on appropriate personal protective equipment.

For more information on waste treatment, refer to Section 13.

SECTION 7: handling and storage

The information contained in this section contains general information and warnings. Refer to the list of Identified Uses in Section 1 for specific information available provided in the exposure scenario (s).

7.1 Precautions for safe handling

: Prevent the development of flammable or explosive vapor concentrations in the air o that exceed the occupational exposure limits.
Also, use the product only in rooms from which all naked flame lamps and other sources of ignition have been removed. Protect electrical equipment according to appropriate standards.
The mixture can become electrostatically charged: always use ground connections when transferring it from one container to another.
Operators must wear antistatic shoes and clothing, while floors must be conductive.
Keep away from sources of heat, sparks and flames. Do not use any tools that cause sparks.
Avoid contact with eyes and skin. Avoid inhalation of dust, particulates, aerosols or mists deriving from the application of this mixture. Avoid inhalation of dust deriving from sandblasting.
It is forbidden to eat, drink and smoke in areas where the material is handled, stored or treated.
Put on appropriate personal protective equipment (see Section 8).
Never empty the product by subjecting it to pressure. The container is not pressurized.
Always keep the material in the original container.
Observe the provisions of the laws relating to health and safety in the workplace.

Do not dispose of the product in the sewer system and water courses. **Information on fire and explosion protection**
Vapors are heavier than air and can spread over floors. Vapors can form explosive mixtures with air.

When the workers, for spraying or other operations, have to work inside the spray booth, the suction conditions are probably insufficient to keep the particulates and solvent vapors under control. In such circumstances they must wear ventilated breathing systems during spraying operations and this until the concentrations of particulate matter and solvent vapors have fallen below the exposure limits.

ALPHALOXAN FLEX

SECTION 7: handling and storage**7.2 Conditions for safe storage, including any incompatibilities**

Store according to local regulations.

Notes on shared storage

Keep away from: oxidizing agents, strong alkalis, strong acids. **Additional information on storage conditions**

Observe the precautions on the label. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. Smoking prohibited. Access prohibited to outsiders. Open containers must be carefully resealed and kept straight to prevent accidental product spillage.

7.3 Specific end uses

Warnings : Unavailable.

Specific guidelines for the industrial sector : Unavailable.

SECTION 8: Exposure controls / personal protection

The information contained in this section contains general information and warnings. The information provided refers to the typical uses envisaged for the product. Additional measures may be needed for bulk processing or other uses that could significantly increase worker exposure or emissions to the environment.

8.1 Control parameters**Occupational exposure limits**

Name of the product / ingredient	Exposure limit values
toluene	Ministry of Labor and Social Policies (Italy, 10/2013). Absorbed through the skin. 8 hours: 50 ppm 8 hours. 8 hours: 192 mg / m ³ 8 hours.
methanol	Ministry of Labor and Social Policies (Italy, 10/2013). Absorbed through the skin. 8 hours: 200 ppm 8 hours. 8 hours: 260 mg / m ³ 8 hours.

**Monitoring Procedures:
Recommended**

If this product contains ingredients with exposure limits, personal, workplace atmosphere and biological monitoring may be required to determine the effectiveness of ventilation or other control measures and / or the need to use protective equipment respiratory. Refer to the monitoring standards, such as the following: European standard EN 689 (Atmosphere in the workplace - Guidance on the assessment of exposure by inhalation to chemical compounds for the purpose of comparison with limit values and measurement strategy) Standard European EN 14042 (Atmospheres in the workplace - Guide to the application and use of procedures for assessing exposure to chemical and biological agents) European standard EN 482 (Atmospheres in

DNEL / DMEL

No DNEL / DMEL available.

PNEC

No PNECs available.

8.2 Exposure controls Appropriate**engineering controls**

:Provide adequate ventilation. When reasonably possible, this can be achieved by means of replacement ventilation and good general aspiration. If it is impossible to keep the concentrations of solvent vapors and powders below the occupational exposure limit, wear suitable means of respiratory protection.

SECTION 8: Exposure controls / personal protection

Individual protection measures

Hygiene measures : Before eating, smoking and using the lavatory and at the end of the working period, wash your hands, arms and face thoroughly after handling chemicals. Appropriate techniques should be used to remove potentially contaminated clothing. Wash the contaminated garments before reusing them. Make sure that the eyewash stations and emergency showers are close to the place of use.

Eye / face protection : Use protective goggles to prevent accidental penetration of liquids into the eyes.

Skin protection

Hand protection

Gloves

: In case of prolonged or frequently repeated contact, a glove with protection class 6 is recommended (breakthrough time > 480 minutes, according to EN374). Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class 2 or higher is recommended (breakthrough time > 30 minutes, according to EN374). Recommended gloves: nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there are signs of damage to the glove material.

The performance or effectiveness of the glove can be reduced by physical / chemical damage and poor maintenance.

Device of body protection : Personnel must wear antistatic clothing made of natural fiber or synthetic fiber resistant to high temperatures.

Other devices of skin protection : Choose appropriate footwear and any additional skin protection measures based on the activity being carried out and the inherent risks. Such choices must be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, use appropriate, certified respirators.

Treatments such as sanding, sandblasting or flame removal, etc., of the paint layers, can generate dangerous dust and / or fumes. Wet sanding should be used wherever possible. Respiratory protection in case of dust or spray mist formation. (particulate filter EN143 type P2) Respiratory protection in case of vapor formation. (half mask with A2-P2 combined filter up to concentrations of 0.5% by volume.)

Environmental exposure controls : Do not dispose of the product in the sewer system and water courses.

SECTION 9: physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Miscellaneous: See
Odor	: label. Unavailable.
Odor threshold	: Unavailable.
pH	: Unavailable.
Melting point / freezing point	: Unavailable.
Initial boiling point and boiling range	: 100 ° C
Flash point	: Not applicable.
Evaporation rate	: Unavailable.
Upper / lower flammability or explosive limits	: Unavailable.
Vapor pressure	: Unavailable.
Vapor density	: Unavailable.

ALPHALOXAN FLEX**SECTION 9: physical and chemical properties**

Relative density	: 1,461
Solubility (the solubilities)	: Easily soluble in the following materials: cold water.
Partition coefficient: noctanol / water	: Unavailable.
Temperature of self-ignition	: Unavailable.
Temperature of decomposition	: Unavailable.
Viscosity	: Kinematic (room temperature): 10.95 cm ² / s Not
Explosive properties	: available.
Oxidizing properties	: Unavailable.
9.2. Other information	
Solubility in water	: Unavailable.

SECTION 10: stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable under the recommended handling and storage conditions (see section 7).
10.3 Possibility of reactions:	Under normal conditions of storage and use, hazardous reactions will not occur. dangerous
10.4 Conditions to avoid	: If exposed to high temperatures it can produce dangerous decomposition products.
10.5 Incompatible materials:	To avoid strong exothermic reactions, keep away from the following materials: oxidizing agents, strong alkalis, strong acids.
10.6 Products of dangerous decomposition	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, nitrogen oxides.

SECTION 11: toxicological information**11.1 Information on toxicological effects**

There are no data available on the mixture itself. The mixture was evaluated following the conventional method of the CLP regulation (EC) No. 1272/2008 and is consequently classified according to its toxicological properties. For more details, see Sections 2 and 3.

Exposure to solvent vapor concentrations above the pre-established occupational limit can be harmful to health, causing irritation of the mucous membranes and respiratory tract with adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, dizziness and wobbling, fatigue, muscle weakness, sleepiness and in extreme cases loss of consciousness.

Solvents may cause some of the aforementioned effects via skin absorption. Repeated or prolonged contact with the mixture can result in the removal of natural skin fat, resulting in non-allergic contact dermatitis and absorption through the skin.

Contact of the liquid with the eyes can cause irritation and reversible damage.

Ingestion can cause nausea, diarrhea and vomiting.

If known, the delayed and immediate effects, as well as the chronic effects of the components deriving from short and long-term exposure, by the oral and dermal route, by inhalation and by contact with the eyes, are taken into account.

Contains 1,2-benzisothiazol-3 (2H) -one, 2-octyl-2H-isothiazol-3-one, C (M) IT / MIT (3: 1). It can cause an allergic reaction.

Acute toxicity

ALPHALOXAN FLEX

SECTION 11: toxicological information

Product name/ ingredient	Result	Species	Dose	Exposure
methanol	LD50 Through the skin	Rabbit	15800 mg / kg	-
	LD50 Intraperitoneal	Piggy of India	3556 mg / kg	-
	LD50 Intraperitoneal	Hamster	8555 mg / kg	-
	LD50 Intraperitoneal	Mouse	10765 mg / kg	-
	LD50 Intraperitoneal	Rabbit	1826 mg / kg	-
	LD50 Intraperitoneal	Rat	7529 mg / kg	-
	DL50 Intravenous	Mouse	4710 mg / kg	-
	DL50 Intravenous	Rabbit	8907 mg / kg	-
	DL50 Intravenous	Rat	2131 mg / kg	-
	LD50 Oral LD50	Dog	7500 mg / kg	-
	Oral LD50 Oral	Ape	7 g / kg	-
	LD50 Oral LD50	Ape	7000 mg / kg	-
	Oral LD50 Oral	Mouse	5800 mg / kg	-
	LD50 Oral LD50	Pig	> 5000 mg / kg	-
	Subcutaneous	Rabbit	14200 mg / kg	-
		Rat	5600 mg / kg	-
		Mouse	9800 mg / kg	-
	LDLo Dermal LDLo	Ape	393 mg / kg	-
	Intravenous	Cat	4641 mg / kg	-
	LDLo Oral LDLo	Dog	7500 mg / kg	-
	Oral LDLo Oral	Human	428 mg / kg	-
	LDLo Oral	Human	143 mg / kg	-
		Man - Male	14 mL / kg	-
	LDLo Orally	Man - Male	6422 mg / kg	-
	LDLo Oral LDLo	Ape	5000 mg / kg	-
	Oral LDLo Oral	Mouse	420 mg / kg	-
	LDLo Oral	Rabbit	7500 mg / kg	-
		Woman - Female	10 mL / kg	-
	LDLo Parenterale	Frog	59 g / kg	-
	LDLo Exposure path not reported	Man - Male	868 mg / kg	-
	Intraperitoneal TDLo	Rat	3490 mg / kg	-
	Intraperitoneal TDLo	Rat	3000 mg / kg	-
	TDLo Orally	Man - Male	0.43 mL / kg	-
	TDLo Orally	Man - Male	1.14 mL / kg	-
	TDLo Orally	Man - Male	1.4 mL / kg	-
	TDLo Orally	Man - Male	3429 mg / kg	-
	TDLo Orally	Man - Male	3571 uL / kg	-
	TDLo Orally	Man - Male	9450 uL / kg	-
	TDLo Oral TDLo	Rat	8 g / kg	-
	Oral TDLo Oral	Rat	3 g / kg	-
	TDLo Oral TDLo	Rat	3 g / kg	-
	Oral TDLo Oral	Rat	8 mL / kg	-
		Rat	3500 mg / kg	-
		Woman - Female	4 g / kg	-
	TDLo Subcutaneous	Rat	6825 mg / kg	-

Conclusion / Summary :Unavailable.

Acute toxicity estimates

Unavailable.

ALPHALOXAN FLEX

SECTION 11: toxicological information

Irritation / Corrosion

Product name/ ingredient	Result	Species	Score	Exposure	Observation
1,2-benzisothiazol-3 (2H) -one	Skin - Mild irritant	Human	-	48 hours 5	-
Octilnone (ISO)	Eyes - Strongly irritating	Rabbit	-	Percent 100	-
toluene	Eyes - Mild irritant	Rabbit	-	milligrams 0.5 minutes	-
	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Strongly irritating	Rabbit	-	870 Micrograms	-
	Skin - Mild irritant	Pig	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 250 microliters	-
	Skin - Moderately irritating	Rabbit	-	435 milligrams	-
	Skin - Moderately irritating	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderately irritating	Rabbit	-	500 milligrams	-
C (M) IT / MIT (3: 1)	Skin - Severe irritant Eyes - Moderately	Human	-	0.01 Percent	-
methanol	irritating	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderately irritating	Rabbit	-	40 milligrams	-
	Skin - Moderately irritating	Rabbit	-	24 hours 20 milligrams	-

Conclusion / Summary : Unavailable.

Awareness raising

Conclusion / Summary : Unavailable.

Mutagenicity

Conclusion / Summary : Unavailable.

Carcinogenicity

Conclusion / Summary : Unavailable.

Reproductive toxicity

Conclusion / Summary : Unavailable.

Teratogenicity

Conclusion / Summary : Unavailable.

Specific target organ toxicity (STOT) - single exposure Unavailable.

Specific target organ toxicity (STOT) - repeated exposure

Name of the product / ingredient	Category	Via of exposure	Target organs
diuron	Category 2	Not determined	Not determined
zinc pyrithione	Category 1	Orally	Not determined

Aspiration hazard Unavailable.

Other information :Unavailable.

ALPHALOXAN FLEX

SECTION 12: ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Do not dispose of the product in the sewer system and water courses.

The mixture was evaluated following the summation method of the CLP Regulation (EC) No. 1272/2008 and is consequently classified according to its ecotoxicological properties. See Sections 2 and 3 for more details.

Product name/ ingredient	Result	Species	Exposure
diuron	Acute EC50 0.0023 mg / l Fresh water	Algae - Chlorella pyrenoidosa	96 hours
	Acute EC50 2.4 ppb Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 0.005 mg / l Fresh water	Aquatic plants - Lemna sp.	96 hours
	Acute EC50 7.6 µg / l Fresh water	Aquatic plants - Lemna aequinoctialis	72 hours
	Acute EC50 8.6 mg / l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 8.6 mg / l Fresh water	Daphnia - Daphnia magna - Newborn	48 hours
	Acute EC50 8.4 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute IC50 2.41 µg / l Sea water	Aquatic plants - Halodule uninervis	72 hours
	Acute IC50 5.89 µg / l Sea water	Aquatic plants - Halodule uninervis	72 hours
	Acute IC50 2.47 µg / l Sea water	Aquatic plants - Zostera muelleri	72 hours
	Acute LC50 3044 µg / l Sea water	Crustaceans - Palaemon serratus - Zoea	48 hours
	Acute LC50 1.95 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 3100 µg / l Fresh water	Fish - Morone saxatilis Fish -	96 hours
	Acute LC50 2900 µg / l Fresh water	Cyprinus carpio - Fry	96 hours
	Chronic EC10 0.11 µg / l Fresh water	Algae - Fragilaria capucina - Exponential growth phase Algae	96 hours
	Chronic EC10 0.76 µg / l Fresh water	- Fragilaria capucina ssp. rumpens	96 hours
	Chronic IC10 0.47 µg / l Sea water	Aquatic plants - Halodule uninervis	72 hours
	Chronic IC10 0.7 µg / l Sea water	Aquatic plants - Halodule uninervis	72 hours
	Chronic IC10 0.49 µg / l Sea water	Aquatic plants - Zostera muelleri	72 hours
	Chronic NOEC 0.283 µg / l Sea water	Algae - Nitzschia pungens	96 hours
1,2-benzisothiazol-3 (2H) -one	Chronic NOEC 0.34 µg / l Sea water	Aquatic plants - Halodule uninervis	72 hours
	Chronic NOEC 0.34 µg / l Sea water	Aquatic plants - Zostera muelleri	72 hours
	Chronic NOEC 26.4 ppb	Fish - Pimephales promelas Fish -	60 days
	Chronic NOEC 26.4 ppb	- Pimephales promelas Fish -	60 days
Octilnone (ISO)	Chronic NOEC 26.4 ppb	Pimephales promelas Fish -	60 days
	Chronic NOEC 33.4 µg / l Fresh water	Pimephales promelas - Embryo	63 days
	Acute EC50 1.5 mg / l	Daphnia - Daphnia magna	48 hours
	Acute EC50 0.4 mg / l	Daphnia - Pseudomonas putia	16 hours
zinc pyrithione	Acute IC50 0.067 mg / l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute LC50 1.3 mg / l	Fish - Ochorhynchus mykiss	96 hours
	Acute EC50 107 ppb Fresh water	Dafnia - Daphnia magna Fish -	48 hours
	Acute LC50 47 ppb Fresh water	Oncorhynchus mykiss Dafnia -	96 hours
	Chronic NOEC 74 ppb Fresh water	Daphnia magna Fish -	21 days
	Chronic NOEC 8.5 ppb	Pimephales promelas Algae -	35 days
	Acute EC50 0.51 µg / l Sea water	Thalassiosira	96 hours

ALPHALOXAN FLEX

SECTION 12: ecological information

methanol	Acute EC50 8.25 ppb Fresh water Acute LC50 2.68 ppb Fresh water Chronic EC10 0.36 µg / l Sea water	pseudonana Daphnia - Daphnia magna Fish - Pimephales promelas Algae - Thalassiosira pseudonana	48 hours 96 hours 96 hours
	Chronic NOEC 2.7 ppb Fresh water Acute EC50 16.912 mg / l Sea water Acute EC50 24500000 µg / l Fresh water	Daphnia - Daphnia magna Algae - Ulva pertusa Daphnia - Daphnia magna - Larva	21 days 96 hours 48 hours
	Acute EC50 22200 mg / l Fresh water	Daphnia - Daphnia obtusa - Newborn	48 hours
	Acute EC50 12835 mg / l Fresh water Acute EC50 12700000 µg / l Fresh water	Fish - Lepomis macrochirus Fish - Lepomis macrochirus - Juvenile	96 hours 96 hours
	Acute EC50 13000000 µg / l Fresh water	Fish - Oncorhynchus mykiss - Juvenile	96 hours
	Acute LC50 2500000 µg / l Sea water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 3289 mg / l Fresh water	Daphnia - Daphnia magna - Newborn	48 hours
	Acute LC50 15.32 g / l Fresh water	Fish - Oreochromis mossambicus - Adult	96 hours
	Acute LC50 290 mg / l Fresh water	Fish - Danio rerio - Egg Algae -	96 hours
	Chronic NOEC 71 ppm Fresh water	Heterosigma akashiwo Algae -	96 hours
	Chronic NOEC 1400 ppm Fresh water	Skeletonema costatum Algae -	96 hours
	Chronic NOEC 410 ppm Fresh water	Prorocentrum minimum Algae -	96 hours
	Chronic NOEC 24 ppm Fresh water	Eutreptiella sp.	96 hours
	Chronic NOEC 9.96 mg / l Sea water	Algae - Ulva pertusa	96 hours

Conclusion / Summary :Unavailable.

12.2 Persistence and degradability

Conclusion / Summary :Unavailable.

12.3 Bioaccumulative potential

Product name/ ingredient	LogP _{ow}	BCF	Potential
diuron	2.84	5.2	low
Octilnone (ISO)	2.45	-	low
zinc pyriithione	0.9	11	low
toluene	2.73	90	low
methanol	- 0.77	<10	low

12.4 Mobility in soil

Soil / water partition coefficient (K_{oc}) : Unavailable.

Mobility : Unavailable.

12.5 Results of PBT and vPvB PBT

assessment : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects :No known significant effects or critical hazards.

ALPHALOXAN FLEX

SECTION 13: Disposal considerations

The information contained in this section contains general information and warnings. Refer to the list of Identified Uses in Section 1 for specific information available provided in the exposure scenario (s).

13.1 Waste treatment methods**Product**

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products must always be carried out in accordance with the legal indications on environmental protection and waste disposal and the requirements of each relevant local authority. Dispose of surplus and non-recyclable products through an authorized waste disposal company. Untreated waste should not be disposed of in the sewer system unless it fully complies with the requirements of each entity and legislation.
- Hazardous waste** : The classification of the product could meet the criteria for hazardous waste.
- Considerations on the disposal** : Do not dispose of the product in the sewer system and water courses. Dispose of in accordance with applicable regional, state and local laws. If this product is mixed with other wastes, the original refused code can no longer be applied and an appropriate code will need to be assigned. For more information, contact the responsible waste disposal agency.

Packing

- Methods of disposal** : The generation of waste should be avoided or minimized wherever possible. Waste packaging must be recycled. Incineration or landfilling should only be considered when recycling is not practicable.
- Considerations on the disposal** : Using the information provided in this safety data sheet, contact the appropriate waste disposal authority for guidance on the classification of empty containers. Empty containers must be discarded or reprocessed. Dispose of containers contaminated by the product in accordance with local or national regulatory requirements.

Type of packaging	European Waste Catalog
CEPE Paint Guidelines	15 01 10 * packaging containing residues of dangerous substances or contaminated by such substances

- Special precautions** : Do not dispose of the product and the container except with due precautions. Care should be taken when handling emptied containers that have not been cleaned or rinsed. Empty containers or liners can retain product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

The information pertaining to IATA and ADN is considered irrelevant as the material is not packaged in the correct approved packaging required by these modes of transport.

	ADR	IMDG
14.1 UN number	Not regulated.	Not regulated.
14.2 Name of shipment of the UN	Not applicable.	Not applicable.
14.3 Classes of connected danger to transport		

ALPHALOXAN FLEX		
The information pertaining to IATA and ADN is considered irrelevant as the material is not packaged in the correct approved packaging required by these modes of transport.		
Class	Not applicable.	Not applicable.
Secondary class	-	-
14.4 Group of packaging	Not applicable.	Not applicable.
14.5 Dangers for the environment Marine pollutant Substances marine pollutants	No.	No. Unavailable.
14.6 Precautions special for users	Transport within the user's property: always carry out transport with closed containers, stored vertically and secured to the means of transport. Verify the suitability of the persons carrying out the transport to intervene effectively in the event of an accident and / or spill.	
Number of identification of danger or number Kemler Schemes of emergency ("EmS")	Unavailable.	Not applicable.
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	:Not applicable.	
Information additional	-	-

SECTION 15: Regulatory information

15.1 Health, safety and environmental legislation and regulations specific to the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of Extremely Concern None of the components are listed.

Annex XVII - Restrictions:Not applicable. **in the field of manufacturing, placing on the market and use of certain substances, preparations and articles dangerous**

Other EU regulations

ALPHALOXAN FLEX**SECTION 15: Regulatory information**

VOC for ready-to-use mixtures :Not applicable.

Substances harmful to the ozone layer (1005/2009 / EU)

Not in the list.

Prior Inform Consent (PIC - Prior Inform Consent) (649/2012 / UE) Not in the list.

Seveso Directive

This product is not controlled under the Seveso Directive.

National standards

Legislative Decree 152/06

:Not classified.

International Regulations

Chemical Weapons Convention List - Tables I, II and III Chemical Compounds

Not in the list.

Montreal Protocol (Annexes A, B, C, E) Not in the list.

Stockholm Convention on Persistent Organic Pollutants Not in the list.

Rotterdam Convention on Prior Informed Consent (PIC) Not in the list.

UNECE Protocol to the Aarhus Convention on Persistent Organic Pollutants and Heavy Metals Not in the list.

15.2 Evaluation of chemical safety :No chemical safety assessment has been carried out.

SECTION 16: other information

CEPE code :1

Indicates information that has changed from previously issued.

Abbreviations and acronyms :

- ATE = Estimation of Acute Toxicity
- CLP = Classification, Labeling and Packaging [Regulation (EC) No. 1272/2008]
- DMEL = Derived level with minimal effects
- DNEL = Derived No Effect Level
- EUH indication = CLP specific risk provisions
- PBT = Persistent, Bioaccumulative, Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP / GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated hazard statements


<p>H225 H301 H302 H304</p> <p>H310 H311 H314 H315 H317</p>	<p>Highly flammable liquid and vapor. Toxic if ingested. Harmful if swallowed. It can be fatal if swallowed and if it enters the respiratory tract.</p> <p>Fatal in contact with the skin. Toxic in contact with the skin. It causes serious skin burns and serious eye injuries. Causes skin irritation. May cause an allergic skin reaction.</p>
--	--

Date of issue / Date of revision :11-3-2021

ALPHALOXAN FLEX**SECTION 16: other information**

H318	Causes serious eye damage.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H336	It can cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360FD	May damage fertility. It can harm the unborn child.
H361d	Suspected of damaging the unborn child.
H370	It causes damage to organs.
H372 (oral)	Causes damage to organs through prolonged or repeated exposure if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic organisms.
H410	Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
H412	

Full text of classifications [CLP / GHS]

<p>  Acute Tox. 2, H310 Acute Tox. 2, H330 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Acute Tox. 4, H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 3, H412 Asp. Tox. 1, H304 Carc. 2, H351 Eye Dam. 1, H318 Flam. Liq. 2, H225 Repr. 1B, H360FD Repr. 2, H361d Skin Corr. 1B, H314 Skin Corr. 1C, H314 Skin Irrit. 2, H315 Skin Sens. 1, H317 Skin Sens. 1A, H317 STOT RE 1, H372 (oral) STOT RE 2, H373 STOT SE 1, H370 STOT SE 3, H336 </p>	<p> ACUTE TOXICITY (skin) - Category 2 ACUTE TOXICITY (inhalation) - Category 2 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (skin) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 ACUTE TOXICITY (oral) - Category 4 SHORT-TERM (ACUTE) HAZARD TO THE AQUATIC ENVIRONMENT - Category 1 LONG-TERM (CHRONIC) HAZARD TO THE AQUATIC ENVIRONMENT - Category 1 LONG-TERM (CHRONIC) HAZARD TO THE AQUATIC ENVIRONMENT - Category 3 ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE / EYE IRRITATION - Category 1 FLAMMABLE LIQUIDS - Category 2 REPRODUCTION TOXICITY (Fertility and Unborn Child) - Category 1B REPRODUCTION TOXICITY (Unborn child) - Category 2 SKIN CORROSION / IRRITATION - Category 1B SKIN CORROSION / IRRITATION - Category 1C SKIN CORROSION / IRRITATION - Category 2 SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (oral) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 SPECIFIC TOXICITY TO TARGET ORGANS (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcosis) - Category 3 </p>
---	---

Print date : 12-3-2021

Date of issue / Date of revision : 11-3-2021

Date of issue previous one : 31-8-2020

Version : 20

Notice to the reader

SECTION 16: other information

IMPORTANT NOTE. *The information contained in this sheet is not to be considered exhaustive and is based on our current technical knowledge and on the laws in force: anyone who uses the product for purposes other than those specifically suggested in the technical sheet, without having previously obtained our written authorization, does so. at your own risk. It is always the user's responsibility to take all necessary measures to comply with the requirements of local laws. Always read the safety data sheet and the technical data sheet of this product, if available. All suggestions or statements made by us regarding the product (whether in this sheet or otherwise) are correct to the best of our knowledge, however, the quality or condition of the media or the many external factors affecting the use and application of the product are beyond our control. Consequently, in the absence of a specific written agreement, we accept no responsibility for the performance of the product or for any loss or damage resulting from its use. All products and technical advice provided comply with our standard terms and conditions of sale. We recommend that you ask for a copy of this document and read it carefully. The information contained in this sheet is subject to periodic changes, in the light of the experiences acquired and our policy of continuous development. It is the user's responsibility to verify that this sheet is up to date before using the product.*

This data sheet mentions trademarks owned or licensed to AkzoNobel.